NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	
Name Wampler & Werth Farms	county Crook Driller's well number	
Address Powell Butte, Ore. 9775.3	SW 1/2 SE 1/2 Section 11 T. 15S R. 14E W.M.	
Autress J. On Calada Distance of Survey	Bearing and distance from section or subdivision of	corner
(2) TYPE OF WORK (check):	1.420 ft. south and 1,000 ft. east of	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	the center of section 11	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	,
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 52	f
Rotary Driven Domestic Industrial Municipal	Static level 40 ft. below land surfa	ace. Date 3-13-79
Cable Jetted Dug Bored Irrigation Test Well Other	Artesian pressure Ibs. per square in	ich. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below	w casing 12
16 " Diam. from 2 ft. to -19 ft. Gage .250	Depth drilled 97 ft. Depth of completed well 97 ft.	
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and	
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum a	and aquifer penetrate
	with at least one entry for each change of formation position of Static Water Level and indicate principal	. Report each change : al water-bearing strat
PERFORATIONS: Perforated? Yes Ano.		rom To SWL
Type of perforator used	Mari California	0 4
Size of perforations in. by in.	brown sandy soil brown coarse sandstone	4 41
perforations from ft. to it.	grey hard rock	41 52
perforations fromft. toft.	black broken rock WB	52 94 40
perforations from ft. to ft.	grey hard rock	94 97
(7) SCREENS: Well screen installed? Yes Y No		
Manufacturer's Name		
Type Model No.	5	
Diam. Slot size Set from ft. to ft.	RFCFIVF	
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	MAR 2 8 1979	
Was a pump test made? X Yes No If yes, by whom? Jack Abba	WATER RESOURCES DEPT	•
Vield: 480 gal./min. with 7 ft. drawdown after 1 hrs.	SALEM, OREGON	
" "		
" " "		
Bailer test gal./min. with ft. drawdown after hrs.	<u> </u>	
Date: test		
Artesian flow g.p.m. Apperature of water Depth artesian flow encounteredft.	Work started 3-12 179 Completed	3-14 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3-19 19-
Well seal-Material used cement	Drilling Machine Operator's Certification:	
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my	
Diameter of well bore to bottom of seal 20 in.	best knowledge and belief.	
Diameter of well bore below seal 12 in.	[Signed] Jarry Machine Operator)	ate3=17_, 19_
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 678	
How was cement grout placed?pressure grout	Drining Machine Operator & Election 144	
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	
The state of the s	true to the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes ♣ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ⚠ No	Name Crawford Well Drilling, Inc. (Person, firm or corporation) (Type or print)	
	Address 1245 NW Lower Bridge Terrebonne, Ore.	
	Land & Count	nd
Method of sealing strata off Was well gravel packed? ☐ Yes ☒ No Size of gravel:	[Signed] (Water Well Contrac	etor)
Gravel placed fromft. toft.	Contractor's License No. 570 Date	3 - 17, 19.
THE REAL PROPERTY AND ADDRESS OF THE PROPERTY OF THE PARTY OF THE PART	The state of the s	