NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 , witkin 30 days from the date of well completion.

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print)

(Do not write above this line)



State Well No. 156/14E-11 bd

S	tate	Permit	No.	**************************************

(1) OWNER:	(10) LOCATION OF WELL:		
Name Norman Curry	County Crook Driller's well number		
AddressPowell Butte, Oregon	SE 14 NW 14 Section 11 T. 15S	R. 14E W.M.	
	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):	800' N & 725' W of Center 4	corner of	
New Well 🔣 Deepening 🗌 Reconditioning 🗍 Abandon 🗍	S	ec 11	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 46	ft.	
Rotary Driven DokkshXX Industrial Municipal DokkshXX	Static level 46 ft. below land st	urface. Date 3/12/80	
Cable	Artesian pressure lbs. per square		
(5) CASING INSTALLED: Threaded   Welded   X		^	
	1	elow casing 8	
8 "Diam from + 1 ft. to 25 ft. Gage 250 ft. Gage ft. Gage ft. Gage	Depth drilled 98 ft. Depth of comple	eted well 98 ft.	
Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a		
3444 47611	and show thickness and nature of each stratur with at least one entry for each change of format	tion. Report each change in	
(6) PERFORATIONS: Perforated?   Yes  No.	position of Static Water Level and indicate princ	cipal water-bearing strata.	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	brn soil	0 4	
perforations from ft. to ft.	brn congl med	4 9	
perforations from ft. to ft.	brn sand	9 16 16 26	
perforations from ft. to ft.	brn congl med fine grey basalt	16 26 26 46	
(7) SCREENS: Well screen installed?   Yes  No	multi colored congl med(WB)	46 50 46	
Manufacturer's Name	grey basalt w/seams (WB)	50 61	
Type Model No	redish brn basalt (WB)	61 79	
Diam Slot size Set from ft. to ft.	grey basalt (WB)	79 88	
Diam. Slot size from ft. to ft.	lt brn basalt (WB)	88 96	
(8) WELL TESTS: Drawdown is amount water level is	lt brn congl crs	96 98	
lowered below static lever			
Was a pump test made?  Yes No If yes, by whom?			
d: gal./min. with ft. drawdown after hrs.	752 <b>1 1</b> 1980		
At n ld etden 100 CDM with 28 DD			
" Air lifting 100 GPM with 2' DD "	WATER RESOURCES DEPT		
Bailer test gal./min. with ft. drawdown after hrs.	SALEM, OREGON		
esian flow g.p.m.			
Temperature of water 56 Depth artesian flow encountered ft.	Work started 3/11 19 80 Complete		
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3/12 19 8	
Well seal—Material used .Coment	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct supervision	
Diameter of well bore to bottom of sealin.	hest knowledge gand helief // //		
Diameter of well bore below seal in.	[Signed] The bluson	Date 3/19 , 19 8	
Number of sacks of cement used in well seal	(Drilling Machine Operator)  Drilling Machine Operator's License No.		
How was cement grout placed?pumped from 25 toO	Driving machine Operator's Intense No.		
	Water Well Contractor's Certification:		
	This well was drilled under my jurisdi		
Was a drive shoe used? ☐ Yes 🛣 No Plugs Size: location ft.	true to the best of my knowledge and bel	iei.	
Did any strata contain unusable water?   Yes XNo	Name Johnson Well Drilling (Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address 3626 NW Coyner Redmo	nd, Ore	
Method of sealing strata off			
Was well gravel packed? ☐ Yes ▼ No Size of gravel:	[Signed] Water Well Contr	actor)	
Gravel placed fromft. toft.	Contractor's License No. 595 Date	3/19 , 19.8	