CROO

JAN 8-1950 WATER WELL REPORT
STATE ENGINEER STATE OF OREGON
SAIFS: WITH STATE OF OREGON File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

State Permit No. 6-1465

(1) OWNER: Name Pilot Butte Hereford Rongh Ino	(11) WELL TESTS: Drawdown is amount we lowered below static level	
Address Ri. 1, Box 525	Was a pump test made? Yes No If yes, by whom?	<u>} </u>
Prineville Ovegun 975	Yield: 2 (f) gal./min. with /9 ft. drawdown	after hrs.
	25 29 29	
(2) LOCATION OF WELL:	Bailer test) 5 gal./min. with 2 ft. drawdown	- 3 D M.4
County () Owner's number, if any—	Artesian flow g.p.m. Date	arter jo nrs.
NW 1/4 Section 2 T. 105 R. 16 E W.M.	Temperature of water Was a chemical analysis mad	In I Voy II No
Bearing and distance from section or subdivision corner	The state of the s	ic. Li res Li Ro
	(12) WELL LOG: Diameter of well	12 inches.
7	Depth drilled 50 ft. Depth of completed wel	
	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each characteristics.	and structure, and se material in each ange of formation.
	MATERIAL	FROM TO
(3) TYPE OF WORK (check):	- transit	1 5
New Well 🗷 Deepening 🗌 Reconditioning 🗍 Abandon 🗍	Corne arevel	5 26
If abandonment, describe material and procedure in Item 11.	Tire of water	26 29
PROPOSED USE (check): (5) TYPE OF WELL:		29 31
	Sand gravel	3/ 5335
Cable Jetted	(flay	35 47
Irrigation ☐ Test Well ☐ Other ☐ Dug ☐ Bored ☐	France	47 50
(6) CASING INSTALLED: Threaded Welded Z		
12" Diam. from ft. to ft. Gage		
"Diam. fromft. toft. Gage		
" Diam. fromft, toft. Gage		·
(7) PERFORATIONS: Perforated?		
Type of perforator used		
SIZE of perforations in. by in.	<u> </u>	
perforations from 31 ft. to 34 ft.		
2.2 perforations from ft. to ft.		
perforations fromft. toft.		
perforations fromft. toft.		
perforations from ft. to ft.	,	-
(8) SCREENS: Well screen installed ☐ Yes ☒ No		
Manufacturer's Name		
Type Model No		•
Slot size Set from ft. to ft.		
Slot size ft. to ft.	Work started 22 / 19 5.9 Completed 3/	July 1959
(9) CONSTRUCTION:	(10) DITTE	
Was well gravel packed? X Yes No Size of gravel: 54.111	(13) PUMP:	
Gravel placed from 2.8	Manufacturer's Name	jarennennennennennennennennennennen
Was a surface seal provided? Yes No To what depth?	Typ Centrifugal, single Phase 340 K	P. 9
Material used in seal—	Well Driller's Statement:	
Did any strata contain unusable water? Yes X No	This well was drilled under my jurisdiction an	d this nament is
Type of water? Depth of strata	true to the best of my knowledge and belief.	u uns report is
Method of sealing strata off	<u> </u>	
(10) NIAMED I DIVINI C	NAME C. E. HURST	e or print)
(10) WATER LEVELS:	Address 834.5.12 at REDMOND). OPE
Static level ft. below land surface Date		to var production gramme
Artesian pressure lbs. per square inch Date	Driller's well number	
Log Accepted by: Wilst Butt 10 er Ranch	[Signed] CELATIUSST	
1/10 P. + 10 1 CO	(Well Driller)	
Signed Owner, 19	License NoDate	31 1959