RECEIVED

OCT 20 1986

WATER RESOURCES DEPT.
SALEM, OREGON

WATER WELL REPORT

STATE OF OREGON

CROO 2099

State Well No. 15S/16E-5AA

State Permit No.

(1) OWNER:

Name Lester Puckett

Address 1450 Lynn Blvd.

City Prineville State Ore

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air ☐ Driven ☐
Rotary Mud ☐ Dug ☐
Cable ☒ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐
Thermal: Withdrawal ☒ Reinjection ☒

(5) CASING INSTALLED:

Steel ☒ Plastic ☐
Threaded ☐ Welded ☒

6 " Diam. from +1 ft. to 19 ft. Gauge .250

" Diam. from ft. to ft. Gauge

LINER INSTALLED:

" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:

Perforated? ☒ Yes ☐ No

Type of perforator used Cutting torch

Size of perforations 1/16 in. by 6 in.

24 perforations from 18 ft. to 19 ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name

Type Model No.

Diam. Slot Size Set from ft. to ft.

Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

Air test gal./min. with drill stem at ft. hrs.

Bailer test 10 gal./min. with 3 ft. drawdown after 1 hrs.

Artesian flow none g.p.m.

Temperature of water 56 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes ☐ No ☒

Well seal—Material used Bentonite

Well sealed from land surface to 18 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 6 in.

Number of sacks of ~~cement~~ Bentonite used in well seal 4 sacks

How was cement grout placed? Poured dry through tremie pipe

Was pump installed? NO Type HP Depth ft.

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of Water? ~~depth of strata~~

Method of sealing strata off

Was well gravel packed? ☐ Yes ☒ No ~~Size of gravel:~~

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Crook Driller's well number 0026

NW ¼ SE ¼ Section 5 T. 15S R. 16E W.M.

Tax Lot # Lot Blk Subdivision

Address at well location: 1450 Lynn Blvd. Prineville, Ore. 97754

(11) WATER LEVEL: Completed well.

Depth at which water was first found 18 ft.

Static level 10 ft. below land surface. Date 10/16/86

Artesian pressure none lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 20 ft. Depth of completed well 20 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sandy soil	0	8	
Broken clay	8	18	
coarse basalt (water bearing)	18	20	10

Work started 10/16 1986 Completed 10/16 1986

Date well drilling machine moved off of well 10/16 1986

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Archie Fox Date 10/16, 1986

(Drilling Machine Operator)

Drilling Machine Operator's License No. 389

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name ARCHIE FOX, WELL DRILLING

(Person, firm or corporation) (Type or print)

Address PO BOX 246 PRINEVILLE, OREGON 97754

[Signed] Archie Fox

(Water Well Contractor)

Contractor's License No. 444 Date 10/16, 1986

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

SP*12658-690