NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

RECEIVED
MAY 7 1979
(Do not write above this line)

CROO 2104 Crook

State Well No. 15S/16E-5ca

State Permit No.

(1) OWNER: WATER RESOURCES DEPT. SALEM, OREGON
Name Virgil Hill
Address 675 S. Elm Prineville, Ore.

(2) TYPE OF WORK (check):
New Well [X] Deepening [ ] Reconditioning [ ] Abandon [ ]
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary [ ] Driven [ ]
Cable [X] Jetted [ ]
Dug [ ] Bored [ ]

(4) PROPOSED USE (check):
Domestic [X] Industrial [ ] Municipal [ ]
Irrigation [ ] Test Well [ ] Other [ ]

(5) CASING INSTALLED:
Threaded [ ] Welded [X]
6" Diam. from +1 ft. to 30 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? [X] Yes [ ] No.
Type of perforator used TORCH
Size of perforations 1/16 in. by 6 in.
40 perforations from 20 ft. to 30 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? [ ] Yes [X] No
Manufacturer's Name —
Type — Model No. —
Diam. — Slot size — Set from — ft. to — ft.
Diam. — Slot size — Set from — ft. to — ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? [ ] Yes [X] No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 15 gal./min. with 5 ft. drawdown after 1 hrs.
Artesian flow NONE g.p.m. —
Temperature of water 56 Depth artesian flow encountered — ft.

(9) CONSTRUCTION:
Well seal—Material used Cement Grout
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 6 sacks
How was cement grout placed? Poured Thru Tremie Pipe forced from Bottom up.

Was a drive shoe used? [ ] Yes [X] No Plugs Size: location ft.
Did any strata contain unusable water? [ ] Yes [X] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [ ] Yes [X] No Size of gravel: —
Gravel placed from — ft. to ft.

(10) LOCATION OF WELL:
County Driller's well number
N.E ¼ S.W ¼ Section 5 T. 15S R. 16E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 20 ft.
Static level 10 ft. below land surface. Date 4/30/79
Artesian pressure NONE lbs. per square inch. Date —

(12) WELL LOG:
Diameter of well below casing 6"
Depth drilled 30 ft. Depth of completed well 30 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	1	
Gravel & Clay	1	5	
Sand & Gravel	5	12	
Sticky Grey Clay	12	20	10'
Fine Brown Sand	20	30	

Work started 4/30 1979 Completed 4/30 1979
Date well drilling machine moved off of well 4/30 1979

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Curt Clawson (Drilling Machine Operator) Date 4/30, 1979
Drilling Machine Operator's License No. 1237

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Archie Fox Well Drilling (Person, firm or corporation) (Type or print)
Address Rt. 1, Box 780 Prineville, Ore.
[Signed] Archie Fox (Water Well Contractor)
Contractor's License No. 444 Date 4/30, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119