NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

CROO 2111

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
OCT 18 1976
WATER RESOURCES DEPT.

State Well No. 15S/16E-5 9b
State Permit No.

(1) OWNER:
Name MIROSLAV PERNICKA
Address 505 E 1st, PRINEVILLE, ORE.

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☒
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☒ Lawn & Shrubs

CASING INSTALLED:
Threaded ☒ Welded ☐
1½" Diam. from 5 ft. to 18½ ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☒ Yes ☐ No
Manufacturer's Name
Type SANOPT. Model No.
Diam. 1½ Slot size Set from 15½ ft. to 18½ ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used CEMENT
Well sealed from land surface to -8 ft.
Diameter of well bore to bottom of seal — in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County CROOK Driller's well number
NW ¼ NE ¼ Section 5 T. 15S R. 16E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 12 ft.
Static level 12 ft. below land surface. Date AUG 76
Artesian pressure — lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing
Depth drilled ft. Depth of completed well ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SANOFT IN BASEMENT TO BE USED FOR SPRINKLING LAWN CITY WATER FOR HOUSE HOLD USE CEMENT BASEMENT WALLS TO -8 TO BE USED AS SEAL			
J.K. WELL INSPECTOR DIST 11			

Work started AUG 1976 Completed AUG 1976
Date well drilling machine moved off of well 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date , 19
(Drilling Machine Operator)
Drilling Machine Operator's License No.

Water Well Contractor's Certification: LANDOWNER

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name
(Person, firm or corporation) (Type or print)
Address
[Signed]
(Water Well Contractor)
Contractor's License No. Date , 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119