

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

RECEIVED WATER WELL REPORT
MAY 1 - 1972 STATE OF OREGON
STATE ENGINEER, SALEM, OREGON 97310
(Please type or print)
STATE ENGINEER
SALEM, OREGON

CROO
2694

State Well No. 16/17-29
State Permit No.

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

(1) OWNER:

Name Bruce Miller
Address Box 15 Deerite Falls, Wash.

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded

6" Diam. from 0 ft. to 100 ft. Gage 1250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

Type of perforator used cutting torch
Size of perforations 1/16 in. by 6 in.
33 perforations from 30 ft. to 100 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name W. O. M.
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Baller test 10 gal./min. with 30 ft. drawdown after 1 hrs.
Artesian flow none g.p.m.
Temperature of water Depth artesian flow encountered none ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
Well sealed from land surface to 1.8 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 0 sacks
Number of sacks of bentonite used in well seal 2 sacks
Brand name of bentonite Central Oregon Bentonite
Number of pounds of bentonite per 100 gallons of water Dry lbs./100 gals.
Was a drive shoe used? Yes No Plugs 40 Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel: ft.
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Crook Driller's well number 161
1/4 Section 29 T. 16 S R. 17 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 35 ft.
Static level 30 ft. below land surface. Date 4/14/72
Artesian pressure none lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6"

Depth drilled 110 ft. Depth of completed well 110 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
top soil	0	14	
brown clay	14	17	
red clay	17	25	
yellow clay	25	35	
sand & gravel (water bearing)	35	65	30
green clay	65	100	30
green rock	100	110	30

Work started 4/13 1972 Completed 4/14 1972
Date well drilling machine moved off of well 4/14 1972

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Archie Fox Date 4/15, 1972
(Drilling Machine Operator)
Drilling Machine Operator's License No. 389

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Archie Fox Well Drilling
(Person, firm or corporation) (Type or print)
Address Rty Box 449 Prineville Ore 97254
[Signed] Archie Fox
(Water Well Contractor)
Contractor's License No. 444 Date 4/15, 1972