NOTICE TO WATER WELL CONTRACTOR  The original and first copy of this report are to be filled with the	LL REPORT State Well No. 16/17-33 L
STATE ENGINEER, SALEM, OREGON 27317 ENGINEER TATE OF within 30 days from the date of well completion.	FOREGONA (IDAA)
(1) OWNER:  Name MELVIN BILYEL & HOWARD FALL  Address 1000 HASIENDA LANE	Drawdown is amount water level is lowered below static level  Was a nump test made? ☐ Yes No If yes, by whom?  Yield: gal/min with ft. drawdown after hrs.
(2) LOCATION OF WELL:	" apro y " " " "  Bailer test 30 gal./min. with 30 ft. drawdown after 2 hrs.
County CROOK Driller's well number  NE, 4 S.W. 4 Section 33 T. 165 R. 17E. W.M.  Bearing and distance from section or subdivision corner  Jaspen Knolls Home Sites  Lat 26 Block 2	Artesian flow  g.p.m. Date  Temperature of water 54 Was a chemical analysis made?   West No  (12) WELL LOG: Diameter of well below casing  Depth drilled 204 ft.  Formation: Describe by color, character, size of material and structure, and show thickness of aquifiers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
	MATERIAL FROM TO
(3) TYPE OF WORK (check):  Well   Deepening   Reconditioning   Abandon   bandonment, describe material and procedure in Item 12.	Shattered Shale Rock 2 38
(4) PROPOSED USE (check):    Domestic   Industrial   Municipal   Cable   Driven   Cable   Jetted   Cable   Cab	Drey hard rock 38 143
Irrigation □ Test Well □ Other □ Dug □ Bored □  (6) CASING INSTALLED: Threaded □ Welded   (7)	Redish hard rock 143 176
	Drey Nork Milium 176 204
(7) PERFORATIONS: Perforated?   Yes Y No	
Type of perforator used           Size of perforations         in. by         in.           perforations from         ft. to         ft.	
(8) SCREENS: Well screen installed? ☐ Yes INO	
Manufacturer's Name Model No.  Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	Work started 5-20 1964. Completed 6-7 1966.  Date well drilling machine moved off of well 6-8 1966.  (13) PUMP:
Well seal—Material used in seal BENTONIE  Depth of seal 40 ft. Was a packer used? NO	Manufacturer's Name FAIR DANKS MORSE  Type: SUDMERSIBLE H.P. 3 Reference
Diameter of well bore to bottom of sealin.  Were any loose strata cemented off?   Was a drive shoe used?   Yes No Size of gravel:	Water Well Contractor's Certification:  This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Gravel placed fromft. toft.  Did any strata contain unusuable water? ☐ Yes No  Type of water? depth of strata	DICK AKINS WELL DRILLING  NAME Presson, Row 2004 ton) (Type or print)  Address PRINEVILLE; OREGON
Method of sealing strata off (10) WATER LEVELS:	Drilling Machine Operator's License No. 249
Static level 166 ft. below land surface Date 6-864  Artesian pressure — lbs. per square inch Date	[Signed] (Water Well Contractor)  Contractor's License No. 261 Date 7 1965

(USE ADDITIONAL SHEETS IF NECESSARY)