NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
STATE ENGINEER, SALEM, OREGON, within 30 days from the date of well completion.

NC RECEIVED CC
MAR 22 1974
STATE ENGINEER
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON

(Please type or print) (Do not write above this line)

State Well No. 17S/17E-22
State Permit No. CROOK

(1) OWNER:
Name Jim Porter
Address Bend Oregon 97701

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☐
6" Diam. from +1½ ft. to 18½ ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☐ Yes ☒ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 40 gal./min. with 4 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 54 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite, chilled drive
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 8 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 5 sacks
Brand name of bentonite Larue Jell
Number of pounds of bentonite per 100 gallons of water Bentonite Sealy used in drilling lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Driller's well number
SW ¼ SW¼ Section 22 T. 17 R. 17 E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 35' ft.
Static level 18 ft. below land surface. Date Dec 17
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 8
Depth drilled 80 ft. Depth of completed well 80 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Over Burden	0	4	
Brown Clay	4	24	
Yellow Clay, (Crumbly)	24	36	18'
Tan Clay	36	57	
Brown Lava	57	80	

Work started Dec 10 1973 Completed Dec 17 1973
Date well drilling machine moved off of well Dec 17 1973

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Forrest Hall (Drilling Machine Operator) Date Dec 17, 1973
Drilling Machine Operator's License No. 558

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name W & H Drilling Co. (Person, firm or corporation) (Type or print)
Address PO Box 51, Redmond,
[Signed] Forrest Hall (Water Well Contractor)
Contractor's License No. 488 Date Dec. 17, 1973

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119