NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion. WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. / 25 | 172-30 cc

(1) OWNER:	(10) LOCATION OF WELL:
Name CARL BRIEKEN	County CANOK Driller's well number
Address RSR 250	JE 14 5414 Section 30 T. 175 R. 17F W.M.
PRINEUILLE OREGON	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 32 ft.
Rotary Driven Domestic Industrial Municipal	Static level 23 ft. below land surface. Date OCT 8-
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
6 " Diam. from 0 ft. to 40 ft. Gage .250	Depth drilled 40 ft. Depth of completed well 40 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials:
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
(6) PERFORATIONS: Perforated? We Yes I No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used Taylock	MATERIAL, From To SWL
Size of perforations in. by 6 in.	BROWN SANDY CLAY 0 32
725 perforations from 25 ft. to 40 ft. perforations from ft. to ft.	BROWN CLAY & GRAVEL 32 38
perforations from ft. to ft.	FINE GRAVES 38 40
	(WATER BEARING)
(7) SCREENS: Well screen installed? Yes X No	
Manufacturer's Name	Augustin and the second of the
Type Model No Diam Slot size Set from ft. to ft.	DECEIVED
Diam. Slot size Set from ft. to ft.	11 L V L 1070
	OCT 25 1979
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	WATER RESOURCES DEPT
s a pump test made? Yes No If yes, by whom?	SALEM, OREGON
Yield: gal./min. with ft. drawdown after hrs.	
" " " " " " " " " " " " " " " " " " "	
11 11 11 11 11 11 11 11 11 11 11 11 11	
eler test 45 gal./min. with / ft. drawdown after / hrs.	
Artesian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started Oct 7 1979 Completed & 7 8 1979
(9) CONSTRUCTION:	Date well drilling machine moved off of well Oct 9 1979
Well seal-Material used FORTLAND CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Robert Skler Date Oct // 1979
Number of sacks of cement used in well seal sacks How was cement grout placed?	(Drilling Machine Operator) Drilling Machine Operator's License No. 764
1.4	Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes I No	Name PILCHER WELL DRILLING (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 577 S. Knight Princy Ile OR
Method of sealing strata off	01 7011
Was well gravel packed? ☐ Yes ¶ No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 698 Date 067 M 1979
(YYGT - N	19.4.7