NOTICE TO WATER WELL CONTRICTOR  The original and first copy of the resonance to be filed with the WATER WELL	L REPORT Bend Copin	17/23-0	2ce
1079 cmann on	anna de la company de la compa	6422	200
SALEM, OREGON 97310			
within 30 days from the date RESOURCES Date of well completion, ATER RESOURCES not write above this line)			
SALEM, OREGUN	8/, 00,	1990	<u>' ]</u>
(1) OWNER:	(10) LQCATION OF WELL:		
Name ROLF KLEINSCHMIDT	County CROOK Driller's well number		
Address P. O. Box 27	SW 1/2 SW 1/2 Section 2 T. 165 R. 238 W.M.		
PANLINA, OR 9775/	Bearing and distance from section or subdivision corner 5		
(2) TYPE OF WORK (check):	350 E OF SW CORNER OF SEC Z		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	- Anna Correction		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	70		
Rotery M Driven D	Depth at which water was first found ft.		
Cable  Jetted  Domestic  Industrial  Municipal			
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Welded (12) WELL LOG: Diameter of well below casing 8			211
72 " Diam. from # ft. to -205 ft. Gage 350	Landing of their policy capital management of		
ft. Gageft.	Depth drilled 750 ft. Depth of completed well 750 ft.		
ft. toft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum		
PERFORATIONS: Perforated? T Ves VNo.	with at least one entry for each change of format	ion. Report each	change in
Terrorated. El Test Mino.	position of Static Water Level and indicate princ		
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.		5/0 557	
perforations from ft. to ft.	11 " NERY BRKD	557062	
perforations from		562 595	
perforations from ft. toft.		607 632	<del></del>
(7) SCREENS: Well screen installed?  Well screen installed?  Yes	HD BEKN BOER	632 711	
Manufacturer's Name	MED HOVERYBERN ROCK W/B	711 732	
Type Model No	HD FRAMESDGRAY POEK	732 750	
Diam. Slot size ft. to ft.	Ξ		
Diam. Slot size Set from ft. to ft.		205 / 7	<u> </u>
(8) WELL TESTS: Drawdown is amount water level is		ATION FR	D 198
lowered below static level	156' TO 198'		<del></del> -
Was a pump test made?  Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			<del></del>
" " "	And the second s		<del></del> =: .
" " " "			
miler test 1000 gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
perature of water 2 Depth artesian flow encountered ft.	Work started / 0 - 3 / 1978 Complete	d 12-21	1978
(9) CONSTRUCTION:	Date well drilling machine moved off of well	12-21	1978
Well seal-Material used WDISTURBED	Drilling Machine Operator's Certification:		
Well sealed from land surface toft.	This well was constructed under my		
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and behief.	above are true	to my
Diameter of well bore below sealin.	[Signed] Delly Williams Date 1979		
Number of sacks of cement used in well seal sacks	(Drilding Machine Operator)		
How was cement grout placed?	Drilling Machine Operator's License No		
	Water Well Contractor's Certification:	. #	•
Word of driver short words of the first state of the stat	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used?  Yes No Plugs Size: location	Name W.D. Williams		
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)  Address 3790 NW. DAKLN LEDWIND (D. 9775)		
Type of water? depth of strata	Address 3790 NW. VAKLN KEDMEND OR 97756		
Method of sealing strata off	[Signed] William W. Williams		
Was well gravel packed? ☐ Yes No Size of gravel:	(Water Well Contra		סר
Gravel placed from ft. to ft.	Contractor's License No. 6 3 Date		., 19.//