NOTICE TO WATER WELL CONTRACTOR The original and first copy of this pod.  are to be filed with the  WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date  WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 WITH 30 days from the date	or print) State Well No.		
of well completion. WATER RESOURCES of with about the sale of well completion.	ove this line)		
SALEM, OREGON			
(1) OWNER:	(10) LOCATION OF WELL:		
Name ROLF KLEINSCHMIDT	County ( ROOK Driller's well number	<u> </u>	
Address 20, Box 27	SE 14 NE 14 Section 4 T. 175 R. 3	23 <i>E</i> W.M.	
PAULINA OR, 97751	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	1300 FT WEST & 200 FT SOUTH OF NE CORNER OF		
New Well ⚠ Deepening □ Reconditioning □ Abandon □	SEC 4		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):			
Potoner [] Deiron []	Depth at which water was first found & ft.		
Cable 🕱 Jetted 🗆 Domestic 🗀 industrial 🗓 Municipal 📋	Static level 5 ft. below land surface. Date		
Dug	Artesian pressure lbs. per square inch. Date		
CASING INSTALLED: Threaded   Welded X   12 "Diam. from #   ft. to = 144 ft. Gage   250	(12) WELL LOG: Diameter of well below casing		
"Diam. fromft. toft. Gage	Depth drilled 239 ft. Depth of completed well 239 ft.		
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;		
ANALYSI ANALYS	and show thickness and nature of each stratum and aquifer penetrated, — with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated?   Yes No.	position of Static Water Level and indicate principal		
Type of perforator used	MATERIAL From	m To SWL	
Size of perforations in. by in.	BRN FINE Soil	) 4	
	GRAVEL CONGLOMERAGE 4	5-4 W/B	
perforations fromft. toft.	BROWN + TAN CLAY 54	, <del>-</del>	
perforations from	WHITE PAMICS 230	1727	
perforations from ft. to ft.	GRAY ROCK 23	7 239	
(7) SCREENS: Well screen installed?   Yes No			
Manufacturer's Name			
Type Model No.	WELL CASING DRIVEN 4 At.	into Clan	
Diam ft. to ft.	140'TO 144 PT. to HELP SEAL, C		
Diam Slot size	SURPACE WATER : WELL HAS	16" HOLE	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Doilles to 140' + 8" Hove Driles	From 140'_	
Was a pump test made? Yes [] No If yes, by whom?			
Yield: 920 gal./min. with 120 ft. drawdown after 8 hrs.	-		
Dellan feek mel (min with the drawdown often bur			
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.		4 ====	
perature of water 60 Depth artesian flow encountered ft.	Work started // 1978 Completed //	<u>- 16 1978</u>	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	- 16 1978	
Well seal—Material used PORTLAND CEMENT. TWAF LATT Well sealed from land surface to	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal	(1) (0) (1) (0) (1) (1) (1) (1)		
Number of sacks of cement used in well seal	(Drilling Machine Operator)		
How was cement grout placed? GRAVITY FLOW	Drilling Machine Operator's License No	64	
nuo cement grout praceur ministration. Amedication ministration in the content of		· · · · · · · · · · · · · · · · · · ·	
1	Water Well Contractor's Certification:	<del>-</del> -	
Was a drive shoe used?   Yes No Plugs Size: location ft.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Did any strata contain unusable water? Yes	Name William D. William S. (Person, firm or corporation)	(Type or print)	
Type of water? Suggest depth of strata 4 70 -54	Address 3780 J. W. OAK LU REDMAND		
Method of sealing strata off Coment Grount OF CASING THE CANY	[Signed] William D. Williams	·	
Was well gravel packed? Tyes No Size of gravel:	(Water Well Contractor)	mar'	
Gravel placed from ft. to ft.	Contractor's License No. 645 Date 11-1	16 , 1970	