NOTICE TO WATER WELL CONTRACTOR: The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED FEB 7 1975 STATE ENGINEER SALEM, OREGON

RECEIVED OCT 31 1974 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT

STATE OF OREGON (Please type or print) (Do not write above this line)

State Well No. 19S/19E-2 aa CROOK 2905

State Permit No. G 6814

(1) OWNER:

Name Ray Richmon

Address Roberts Rt. Box 420 Prineville, Oregon

(2) TYPE OF WORK (check):

New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☑ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☑

12 " Diam. from 0 ft. to 39 ft. Gage .250

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No

Type of perforator used

Size of perforations in. by in.

perforations from ft. to ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☑ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

" " " "

Bailer test 80 gal./min. with 50 ft. drawdown after 2½ hrs.

Artesian flow — g.p.m. —

Temperature of water 54 Depth artesian flow encountered — ft.

(9) CONSTRUCTION:

Well seal—Material used Cement

Well sealed from land surface to 39 ft.

Diameter of well bore to bottom of seal 16 in.

Diameter of well bore below seal 12 in.

Number of sacks of cement used in well seal 19 sacks

Number of sacks of bentonite used in well seal — sacks

Brand name of bentonite —

Number of pounds of bentonite per 100 gallons of water — lbs./100 gals.

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☒ No

Type of water? — depth of strata —

Method of sealing strata off —

Was well gravel packed? ☐ Yes ☒ No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Crook Driller's well number

NE ¼ SW ¼ Section 2 T. 19S R. 19E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 197 ft.

Static level 19 ft. below land surface. Date 5-8-74

Artesian pressure — lbs. per square inch. Date —

(12) WELL LOG:

Diameter of well below casing 12"

Depth drilled 250 ft. Depth of completed well 250 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Overburden	0	2	
Clay - Brown	2	34	19
Lava	34	53	
Clay - Gray	53	97	
Clay - Br.	97	123	
Clay - Gray	123	177	
Lava	177	250	

Work started 4-15 1974 Completed 5-8 1974

Date well drilling machine moved off of well 5-8- 1974

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Fred Gordon Davidson Date 6-16, 1974
(Drilling Machine Operator)

Drilling Machine Operator's License No. 685

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name DAVIDSON DRILLING
(Person, firm or corporation) (Type or print)

Address 626 NW Pershall - Redmond, Ore.

[Signed] Fred Gordon Davidson
(Water Well Contractor)

Contractor's License No. 548 Date 6-16, 1974

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119