## STATE OF OREGON

WATER SUPPLY WELL REPORTCIOD (as required by ORS 537.765) 50162

## RECEIVED

NOV - 6 1995

145/17E/26AD
--------------

WATER RESOURCE (START CARD) # 74271

Instructions for completing this report are on the last page of this form.	T SALEM, OREGON	<del></del>	<del>,</del>		
(1) OWNER: Well Number #6	(9) LOCATION OF	WELL by legal desci	ription:		
Name FALV TUMPKET	County Clock	Latitude	Lor	ngitude	
Address 281,050 E HWY 26 City / 14600		N or Range_			/. WM.
City KINGOUR State OR Zip 97759		SK1/4			
(2) TYPE OF WORK	Tax Lot 2600 L	otBlock	Si	ubdivision	4.000
New Well Deepening Alteration (repair/recondition) Abandonment	Street Address of Wel	l (or nearest address)	MILL	K CEN	KYEG
(3) DRILL METHOD:	(10) STATIC WATER	DIEVEI.	<u> </u>		
Rotary Air Rotary Mud Cable Auger	#2 ft. beld		1	Date	17/95
Other  (4) PROPOSED USE:		lb. per squar		Date 2//	7/95
Domestic Community Industrial Irrigation	(11) WATER BEARI				7
Thermal Injection Livestock Other					
(5) BORE HOLE CONSTRUCTION:	Depth at which water was	s first found	<u> 6                                    </u>		
Special Construction approval Yes No Depth of Completed Well	.	· · · · · · · · · · · · · · · · · · ·			
Explosives used Yes No Type Amount	From To		Estimated Flow Rate		SWL
HOLE SEAL	440 '	540	150	+open	+2
Diameter From To Material From To Sacks or pounds					
12 0 50 CEMENT 0 50 35 SACKS					<del></del>
7" 7 111					
8" 50 610	(10) WELL LOC:	4			
How was seal placed: Method A B C D E	(12) WELL LOG:	l Elevation			
Other Type III Charles Pumper W/Termail					
Backfill placed from ft. to ft. Material	Materia	al	From	То	SWL
Gravel placed from ft. to ft. Size of gravel	CLAY + FKAY	KLS	0	3/	
(6) CASING/LINER:	GRAY CEAKS	TONE	3/	47	
Diameter From To Gauge Steel Plastic Welded Threaded	GRAY BASA	T A	47	365	. 0
Casing: 8" +2 80 250 2	GREEN SAS	ALT MILO	345	410	+2
	HARD BUILD	K BHSHEY	590	610	
	BROWN CLAY	VSTONE	570	610	
Liner: 6" 0 540 188 🛭 🗎			<u> </u>		
Liner: 6" 0 540 186 🗵 🗆					
Final location of shoe(s)					
(7) PERFORATIONS/SCREENS:					
Perforations Method FACTORY					
Screens Type Material					
Slot Tele/pipe From To size Number Diameter size Casing Line					· · · ·
440 540 4886 1100 KWG" 6.181 1					
				<u> </u>	<del></del>
				-	
			-		
	.	•		, ,	
(8) WELLTESTS: Minimum testing time is 1 hour	Date started 2/10	/95 Comp	oleted	2/15/9	3
Flowing	(unbonded) Water Well	Constructor Certificat	tion:	77	
Pump Bailer Air Artesian	I certify that the work	I performed on the cons	struction, alte	ration, or aba	indonment
Yield gal/min Drawdown Drill stem at Time	of this well is in compliant Materials used and information	nce with Oregon water's nation reported above at	re true to the	best of my kr	nowledge
1506pm 0 600 1 hr.	and belief.	-			
	-		WWC Nu		
	Signed (bonded) Water Well Co			Date	
Temperature of water 56 Depth Artesian Flow Found 446	-   '			andonment v	work
Was a water analysis done? Yes By whom Too little	nerformed on this well di	for the construction, alturing the construction da	ates reported	above. All w	ork .
Did any strata contain water not suitable for intended use? Too little	performed during this tin construction standards.	ne is in compliance with	Oregon water	er supply well	1
Salty Muddy Odor Colored Other	Construction standards.			umber /55	
Depth of strata:	Signed Signed			Date	1/95
ORIGINAL & FIRST COPY-WATER RESOURCES DEPARTMENT S		RUCTOR THIRD	COPY-CUS	TOMER	/
ORIGINAL & I INST COLI-WILL RESOURCES DELIMINENT				/	