STATE OF OREGON

WATER SUPPLY WELL REPORT

(as required by ORS 537.765)

WELL I.D. # L 53353 START CARD # 104080

Instructions for completing this report are on the last page of this form.					
Instructions for completing this report are on the last page of this form. (1) LAND OWNER Name Guller //Z Co The Well Number 1072 Address PS R 33/0 State OR Zip 97752	(9) LOCATION O	F WELL by legal of	description:		
Name GUTIETTIZ CaTTLE Company	_ County_C700	Latitude	12	.ongitude	
Address PS R 33/D	_ Township	N o Range	= 22	(E) ₀r W. '	WM.
City Post State Of Zip 97752	_ Section 36_	SE_1/4_	ivw	1/4	
(2) TYPE OF WORK	Tax Lot. 300	_LotBloc	k	Subdivision _	
✓ New Well □ Deepening □ Alteration (repair/recondition) □ Abandonment		Well (or nearest address			
	Paulin	+ HWy	·		
(3) DRILL METHOD:	(10) STATIC WAT			\overline{I}	
Rotary Air Rotary Mud Cable Auger		below land surface.		Date <u>4/3</u>	30/02
Other		lb. per	sauare inch	Date	·
(4) PROPOSED USE:					
□ Domestic □ Community □ Industrial □ Irrigation	. (11) WATER BEA				
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	Depth at which water	was first found 2	40		
(5) BORE HOLE CONSTRUCTION:		То		Flow Rate	SWL
Special Construction approval Yes No Depth of Completed Well 287	From				120
Explosives used Yes No Type Amount Amount	240	285	1000		120
HOLE SEAL					+
Diameter From To Material From To Sacks or pounds 120 0 18% Benton Te 0 18% 12	_		 		
15 1/4 18/2 285	_				
12 285 287		<u> </u>	<u> </u>		
/A / (4) A 4 / (4)	(12) WELL LOG	:			
How was seal placed: Method		ound Elevation			
Mother Poured in Dry	_			To	SWL
Backfill placed fromft. toft. Material	- I I	terial	From	To	SWL
Gravel placed fromft. toft. Size of gravel	Hard Blow	1 Sand STone		60	
(6) CASING/LINER:	Hard Grey	BasulT	60	185	
Diameter From To Gauge Steel Plastic Welded Threaded	Hord Brown	n Sand Sione	185	237	
Diameter From To Gauge Steel Plastic Welded Threaded	Hard Frace	Stey Basult	237	283	120
Liner:					
Drive Shoe used ☐ Inside ☐ Outside ☐ None					
Final location of shoe(s)	=				
(7) PERFORATIONS/SCREENS:					
Perforations Method		CIVED			
Screens TypeMaterial	- HEU	i v L			
Slot Tele/pipe From To size Number Diameter size Casing Line	r	1 9 2002			
From To size Number Diameter size Casing Line	MAY				
	MATCH HE	OURCES DEPT			
	SALEN	A OREGON	_		
	i	,		7	
	Date started 4/2	4/02 Co	ompleted 4/	30/02	
(8) WELL TESTS: Minimum testing time is 1 hour Flowing		Vell Constructor Certi		7-7-7-	
□ Pump □ Bailer 🔀 Air □ Artesian		work I performed on the		alteration or a	bandon-
Yield gal/min Drawdown Drill stem at Time	ment of this well is it	compliance with Oreg	on water supply	y well construe	ction
Treid gaz	standards. Materials	ised and information re	ported above ar	e true to the b	est of my
1000 + unknown 285	knowledge and belief		1 A-WWC	Number 18	-83
	Signed Lave	IA Selli	htino,	Number <u> </u>	1/07
		Il Constructor Certific			
Temperature of water Depth Artesian Flow Found		ll Constructor Certific bility for the construction		ar abandonmo	nt work
Was a water analysis done?	nerformed on this we	ll during the construction	on dates reporte	ed above. All v	work
Did any strata contain water not suitable for intended use?	performed during thi	s time is in compliance	with Oregon w	ater supply wo	ell
□ Salty □ Muddy □ Odor □ Colored □ Other	construction standard	ls. This report is true to	the best of my	knowledge an Number	ia belief. ' R4
Depth of strata:	Signed Don	Mother	wwc.i	_ Date	2-02
·	Signed	11/9/0			