STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

03 ₋ 1	1-2009	

WELL LABEL # L	93135
START CARD #	1006230

(1) LAND OWNER Owner Well I.D. 6	(9) LOCATION OF WELL (legal description)		
First Name CHARLES & JULIE Last Name WAIBEL	County Crook Twp 15.00 S N/S Range 14.00 E E/W WM		
Company	Sec <u>33 NE</u> 1/4 of the <u>NW</u> 1/4 Tax Lot <u>200</u>		
Address 8055 SW POWELL BUTTE HWY	Tax Map Number Lot		
City PRINEVILLE State OR Zip 97754	Lat " or DMS or DD Long " or DMS or DD		
(2) TYPE OF WORK New Well Deepening Conversion	Long or DMS or DD		
Alteration (repair/recondition) Abandonment	Street address of well Nearest address 8055 SW POWELL BUTTE HWY		
(3) DRILL METHOD	8033 SW POWELL BUTTE HWT		
Rotary Air Rotary Mud Cable Auger Cable Mud	(10) STATIC WATER LEVEL		
Reverse Rotary Other	Date SWL(psi) + SWL(ft) Existing Well / Predeepening		
(4) PROPOSED USE Domestic Irrigation Community	Completed Well 02-26-2009 419		
Industrial/ Commericial Livestock Dewatering	Flowing Artesian? Dry Hole?		
Thermal Injection Other	WATER BEARING ZONES Depth water was first found 450		
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy	SWL Date From To Est Flow SWL(psi) + SWL(ft)		
Depth of Completed Well <u>500.00</u> ft.	02-26-2009 450 500 500 419		
BORE HOLE SEAL sacks/			
Dia From To Material From To Amt lbs 16 0 18.5 Bentonite 0 18.5 20 S			
16 0 18.5 Bentonite 0 18.5 20 S			
	(11) WELL LOG Ground Flavation		
	Ground Elevation		
How was seal placed: Method A B C D E	Material From To		
Other Poured in Dry	Top Soil		
Backfill placed from ft. to ft. Material	Hard Grey Dasalt 2 58		
Filter pack from ft. to ft. Material Size	Hard Grey Basalt 120 140		
Explosives used: Yes Type Amount	Frac. Grey Basalt 140 163		
(6) CASING/LINER	Hard Grey Basalt 163 210		
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	Hard Brown Sand Stone 210 353		
●	Frac. Grey Basalt 353 371		
$\bigcirc \bullet \boxed{10} \boxed{0} 5 \boxed{500} \boxed{307} \boxed{\bullet} \boxed{\square} \boxed{\square}$	Hard Grey Basalt 371 428		
	Frac. Grey Basalt 428 500		
Shoe Inside Outside Other Location of shoe(s)			
Temp casing Yes Dia From To			
(7) PERFORATIONS/SCREENS			
Perforations Method Rotary Perforator			
Screens Type Material			
Perf/S Casing/ Screen Scrn/slot Slot # of Tele/ creen Liner Dia From To width length slots pipe size	Date Started 01-28-2009 Completed 02-26-2009		
Perf Liner 420 490 .063 1.5 854	(unbonded) Water Well Constructor Certification		
	I certify that the work I performed on the construction, deepening, alteration, or		
	abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to		
	the best of my knowledge and belief.		
(8) WELL TESTS: Minimum testing time is 1 hour	License Number Date		
Pump Bailer Air Flowing Artesian	Electronically Filed		
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	Signed		
500 490 4	(bonded) Water Well Constructor Certification		
	I accept responsibility for the construction, deepening, alteration, or abandonment		
	work performed on this well during the construction dates reported above. All work		
Temperature 68 °F Lab analysis Yes By	performed during this time is in compliance with Oregon water supply well		
Water quality concerns? Yes (describe below)	construction standards. This report is true to the best of my knowledge and belief.		
From To Description Amount Units	License Number1583		
	Electronically Filed Signed DAVID A SCHLIGHTING (F. 51-4)		
	Signed DAVID A SCHLICHTING (E-filed) Contact Info (optional)		
	Contact into (optional)		