STATE OF OREGON WATER SUPPLY WELL REPORT CROO 54507

Page 1 of 2 WELL I.D. LABEL# L 125392 START CARD # 1034969

| (as required by ORS 537.765 & OAR 690-205-0210) | 7/6/2 | 017 | ORIG | NAL LOG | | 1707 | |
|---|--|---|----------------|---------------|-------------|-----------------|--------------------|
| 1) LAND OWNER Owner Well I.D. | | | | | | , | |
| First Name C/O RAY Last Name FALLGREN | (9) LOCATION OF WELL (legal description) | | | | | | |
| Company SUNSET HILLS HOA | | | | _ | | _ | E E/W WM |
| Address PO BOX 831 | | Sec 36 SE 1/4 of the SE 1/4 Tax Lot 322 | | | | | |
| City PRINEVILLE State OR Zip 97754 | version | Tax Map Number Lot 1 | | | | | |
| | iversion | Tax Map Number Lot 1 Lat " or 44.30838889 DMS or DD Long " or -120.74891667 DMS or DD | | | | | |
| Alteration (complete 2a & 10) Abandonment(c | complete 5a) | Long | | or -120.748 | 391667 | | DMS or DD |
| 2a) FRE-ALTERATION Dia + From To Gauge Stl Plstc Wld Thrd | | | eet address of | | | | _ |
| Casing: | | WYOMING DE | | | · | | |
| Material From To Amt sacks/lbs | | PRINEVILLE, | OR | | | | |
| Seal: | F | | | | | | |
| 3) DRILL METHOD | | (10) STATIC | C WATER | | | | |
| Rotary Air Rotary Mud Cable Auger Cable Mud | | Date SWL(psi) + SWL(ft) Existing Well / Pre-Alteration | | | | | |
| Reverse Rotary Other | | Completed Well 6/28/2017 285 | | | | | |
| 4) PROPOSED USE Domestic Irrigation X Community | | completed | | g Artesian? | D1 D1 | ry Hole? | 285 |
| | | | | _ | | · Ш | 150.00 |
| Industrial/Commericial Livestock Dewatering | ľ | WATER BEARI | NG ZONES | Dept | | as first found | |
| ThermalOther | | SWL Date | From | To | Est Flow | SWL(psi) | + SWL(ft) |
| 5) BORE HOLE CONSTRUCTION Special Standard | (Attach copy) | 6/19/2017 | 153 | 158 | 1 | | 139 |
| Depth of Completed Well 557.00 ft. | | 6/22/2017 | 450 | 460 | 8 | | 285 |
| BORE HOLE SEAL | sacks/ | | | | | | |
| Dia From To Material From To | | | | | | | |
| 12 0 176 Bentonite Chips 0 10 | 5 S | | | | | | |
| 8 176 557 Calculated | 5 80 S | | | | • | | |
| Cement 10 176 Calculated | | (11) WELL I | LOG | Ground Elev | ation | | |
| How was seal placed: Method A B X C D | T _E | | Material | Glound Liev | | From | To |
| Other | | CLAY BROKEN BASALTS | | | | 0 | 10 |
| Rackfill placed from ft to ft Material | | CLAY SILTY | T DI IDI ILI | | | 10 | 16 |
| Filter pack from ft. to ft. Material Size | | SHALE ROCK BROKEN BROWN | | | 16 | 42 | |
| | | SHALE CONGLOMERATE | | | 42 | 52 | |
| Explosives used: Yes Type Amount | | CLAY BROWN SOFT | | | 52 | 63 | |
| 5a) ABANDONMENT USING UNHYDRATED BENTONI | ITE | CLAY GRAY | | | | 63 | 72 |
| Proposed Amount Actual Amount | | SILTSTONE SANDY | | | 72 | 133 | |
| 6) CASING/LINER | | GRAVELS BAS | | | | 133 | 158 |
| Casing Liner Dia + From To Gauge Stl Plstc | | CLAYSTONE C | | | | 158 190 | 190 265 |
| $ \begin{array}{c ccccccccccccccccccccccccccccccccccc$ | | CLAYSTONE I | | ' HARD | | 265 | 452 |
| 6 0 557 .188 | | CLAYSTONE (| | | | 452 | 460 |
| | | CLAYSTONE DARK GRAY | | | | 460 | 520 |
| | ! | BASALT | | | | 520 | 557 |
| | | | | | | | |
| Shoe Inside Outside Other Location of shoe(s) | | | | | | | |
| Temp casing Yes Dia From + To | | | | | | + | |
| 7) PERFORATIONS/SCREENS | | | | | | + | |
| Perforations Method MACHINE | | | | | | | |
| Screens Type Material | | Date Started 6 | 5/19/2017 | C | omplete | d 6/28/2017 | |
| Perf/ Casing/ Screen Scrn/slot Slot # of Screen Liner Dia From To width length slots | I | (unbonded) Wa | ater Well Co | structor Ce | rtification | | |
| Screen Liner Dia From To width length slots Perf Liner 6 437 457 .125 3 228 | | | | | | | ng, alteration, or |
| Perf Liner 6 477 497 .125 3 228 | | | | | | | ater supply well |
| Perf Liner 6 517 537 .125 3 228 | | | | | d informa | tion reported | above are true to |
| | | the best of my k | - | l belief. | | | |
| | | License Number | r 758 | | Date | 7/5/2017 | |
| 8) WELL TESTS: Minimum testing time is 1 hour | | C: 1 | | | _ | <u> </u> | |
| Pump Bailer (•) Air Flowing A | Artesian | Signed THO | MAS R PECK | (E-filed) | | | |
| Yield gal/min Drawdown Drill stem/Pump depth Duration (| Г | (bonded) Water | r Well Consti | uctor Certif | ication | | |
| 8 550 1.5 | | ` ′ | | | | ing, alteration | , or abandonmen |
| | | | | | | | above. All world |
| | | performed durin | ng this time | is in compl | iance wit | h Oregon wa | ater supply wel |
| Temperature 61 °F Lab analysis Yes By | | construction star | ndards. This r | eport is true | o the best | of my knowle | edge and belief. |
| | ppm | License Number | r 1720 | | Date 7/5 | 5/2017 | |
| Water quality concerns? Yes (describe below) TDS amount 275 Prom To Description Amount | | | | | | | |
| | | | ABBAS (E-f | | | | |
| | + | Contact Info (op | otional) | | | | |
| ODICINAL WATER DI | ECOLID CEG DI | ED A DTMENT | | | | | |

CROO 54507

7/6/2017

Map of Hole

STATE OF OREGON WELL LOCATION MAP

This map is supplemental to the WATER SUPPLY WELL REPORT

Oregon Water Resources Department

725 Summer St NE, Salem OR 97301 (503)986-0900



LOCATION OF WELL

Latitude: 44.30838889 Datum: WGS84

Longitude: -120.74891667

Township/Range/Section/Quarter-Quarter Section:

WM 14S 16E 36 SESE Address of Well:

WYOMING DR /COMMON GROUND BLK 2

Well Label: 125392 Printed: July 5, 2017

DISCLAIMER: This map is intended to represent the approximate location the well. It is not intended to be construed as survey accurate in any manner.

Provided by well constructor

