NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion. CROO 98
WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)



State Well No.	145-168	-7ab
----------------	---------	------

State Permit No. ....

(1) OWNER:	(10) LOCATION OF WELL:	
Name TEO ANGERSON	County CROOK Driller's well number 79	
Address RT. 1, BOX 796, PRINGUILE, ORE.	N, W 4 N, E 4 Section 7 T. 145 R. 16 E W.M.	<u>1</u>
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner	
New Well  Deepening □ Reconditioning □ Abandon □		
If abandonment, describe material and procedure in Item 12.		-
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.	
	Depth at which water was first found	t.
Jetted Domestic Industrial Municipal	Static level 20 ft. below land surface. Date 12-30-	X
Bored   Irrigation   Test Well   Other	Artesian pressure NONE lbs. per square inch. Date	_
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing	
6" Diam. from + ft. to 85 ft. Gage 1350	Depth drilled \$5 ft. Depth of completed well \$5 ft	t.
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials	_
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated	đ,
(6) PERFORATIONS: Perforated? Yes   No.	with at least one entry for each change of formation. Report each change i position of Static Water Level and indicate principal water-bearing strate	
Type of perforator used Torch	MATERIAL From To SWL	_
Size of perforations 1/16 in. by 8 in.	Top Soil 04	
150 perforations from 25 ft. to 85 ft.	YELLOW CLAY 4 25 20	7
perforations from ft. to ft.	GREY CLAYSTONE 25 42 "	
perforations from ft. to ft.	YELLOW CLAY 42 49 "	
(7) SCREENS: Well screen installed?   Yes   No	PB/UE CLAYSTONE 49 68 "	
A	HARO Blue ClaySTONE 68 85 "	_
Manufacturer's Name Model No		
Diam. Slot size Set from ft. to ft.		_
Diam, Slot size Set from ft. to ft.	3 500m	
(O) THE T DESCRICE Described to consist with the last		_
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	2590M REPER	
a pump test made? Tyes No If yes, by whom?	O THE REAL PROPERTY.	
Yield: gal./min. with ft. drawdown after hrs.	JAN20 1981	_
<i>II</i>	WATER RESOURCES DEPT	<del></del> -
11 11 11 11	SALEM, OREGON	<b>-</b> -
er test 45 gal./min. with 20 ft. drawdown after 2 hrs.	3 112 0014	
ratesian flow NONE g.p.m.		
Temperature of water 6 Depth artesian flow encounteredft.	Work started 12-28 1980 Completed 12-30 198	0
(A) CONSEDUCATION	Date well drilling machine moved off of well 12-30 198	
(9) CONSTRUCTION: Well seal—Material used Cement Grout	7	_
• 6	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision	n.
Well sealed from land surface to	Materials used and information reported above are true to m	
Diameter of well bore below seal	Signed Litt Clauson Date 1-2 1981	)
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	
How was cement grout placed? POURED THRU TREMIE	Drilling Machine Operator's License No. 1237	tere otto
PIPE, PLACED FROM BOTTOM-UP	Tiroton Tiroton Combination Combination	
	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and helief.	.వ
Was a drive shoe used?  Yes No Plugs Size: location ft.	Name CIAUSON WELL ORILING	
Did any strata contain unusable water?   Yes No	(Person, firm or corporation)  Address RT. 1. BOX 780 PRINCUITE, ON	or.
Type of water? depth of strata	Address R1 1, BOX 100 1 RINCO(1) E ON	
Method of sealing strata off	[Signed] Cut Clauson	د محمد
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contractor)	ر د
Gravel placed from ft to ft	Contractor's License No. 4 Data C	