NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

001189
CURR

State Well No. 32S/15W-36

State Permit No.

(1) OWNER:
Name Francis Carrington
Address 1309 College Ave
Santa Rosa Calif. 95404

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☒
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: NONE Threaded ☐ Welded ☐
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " "
" " "
Bailer test 0 gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite & Cement
Well sealed from land surface to 25' ft.
Diameter of well bore to bottom of seal 6 in.
Diameter of well bore below seal 0 in.
Number of sacks of cement used in well seal 2 sacks
Number of sacks of bentonite used in well seal 1½ sacks
Brand name of bentonite Yellowstone
Number of pounds of bentonite per 100 gallons of water 100 lb/50 gal lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Curry Driller's well number
NE ¼ NW ¼ Section 36 T. 32S R. 15W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found NONE ft.
Static level — ft. below land surface. Date 12-18
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 0
Depth drilled 25 ft. Depth of completed well 0 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Clay soil brown	0	2	
Clay brown	2	12	
Clay & gravel	12	20	
Serpentine conglomerate	20	25	

RECEIVED
JAN 06 1976
WATER RESOURCES DEPT.
SALEM, OREGON

Work started 12-17 1975 Completed 12-18 1975
Date well drilling machine moved off of well 12-18 1975

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Andrew W. Miller (Drilling Machine Operator) Date 12-26, 1975
Drilling Machine Operator's License No. 469

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name George R Miller & Son (Person, firm or corporation) (Type or print)
Address Route 1 Box 770 Bandon Ore
[Signed] Andrew W. Miller (Water Well Contractor)
Contractor's License No. 600 Date 12-26, 1975

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119