RECEIVED

WATER WELL REPORT

JUN 3 1981

STATE OF OREGON	_
(422)	nea
(CURB)	, 3.5 6.6

WATER RESOURCES DEPT SALEM, OREGON

State Well No. 40/13W-26 ac

	•
State Permit No.	

(1) OWNER:	(10) LOCATION OF WELL:
Name Upper Chetco School District #23	County Curry Driller's well number
Address 99603 No Bank Chetco Road	S.W. 14 NE 4 Section 26 T. 40 R. 13 W W.M.
City Brookings, Stater, 97415	Tax Lot #1004 Lot Blk Subdivision
(2) TYPE OF WORK (check):	Address at well location: N. Fork of Chetco River
tr	
New Well ☑. Deepening □ Reconditioning □ Abandon □ If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
	Donth at which water was find to an 20 00 20
(3) TYPE OF WELL: (4) PROPOSED USE (check):	10,
Rotary Air Driven Domestic Industrial Municipal	Static level 15 ft. below land surface. Date 5/28/8 Artesian pressure lbs. per square inch. Date
Rotary Mud Dug Irrigation Test Well Other A Bored Thermal: Withdrawal Reinjection	- Spot Squad Mott. Date
Tongotton D	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel A Plastic Threaded Welded	Depth drilled 36 ft. Depth of completed well 36 ft.
Threaded Welded Welded Welded Welded Threaded Welded Welded Threaded Welded Threaded Welded Welded Welded Welded Welded Threaded Welded Weld	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED:	and indicate principal water-bearing strata.
	MATERIAL From To SWL
	River loam silt clay mixed 0 15 0
(6) PERFORATIONS: Perforated? The Yes I No	holds open hole
Type of perforator used	Hard packed clay, sand gravel 15 20 0
Size of perforations $3/16$ in. by $1\frac{1}{2}$ in. 10ng	inbedded holds open hole
"spaced on 3 sides perforations from 36 ft. to 28 ft.	hard packed solid brown clay 20 26 0
perforations from ft. to ft.	no sand holds open hole
perforations from ft. to ft.	course sand brown gravel course 26 30 15
(7) SCREENS: Well screen installed? \[\subseteq \text{Yes} \textsquare \text{Yo} \]	15 gpm at this point
Manufacturer's Name	light brown clay, light brown 30 33 15
Type Model No.	sand mixed
Diam. Slot Size Set from ft. to ft.	brown fine sand mixed light 33 35 15
Diam. Slot Size Set from ft. to ft.	brown clay. 40 gpm. "
Drawdown is amount water level is lowered	40 gpm. No draw down
below static level	
Was a pump test made? ☐ Yes ☒ No If yes, by whom?	
l: gal./min. with ft, drawdown after hrs.	
" " "	
Air test gal./min. with drill stem at ft. hrs.	
baller test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started may 15 19 81 Completed May 28 19 81
(9) CONSTRUCTION: Special standards: Yes □ No ☼	Date well drilling machine moved off of well May 27 1981
Well seal—Material used Concrete grout	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of sealin.	and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Low Date 5/28, 1981.
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 823.
How was cement grout placed? Forced by 1½ tremie from	
ottom upward	Water Well Contractor's Certification:
Was nump installed?	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was pump installed?	Name McCoy's Water Well Drilling
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location	(Person, firm or corporation) (Type or print)
Type of Water? depth of strata	Address P.9. Fox 1900, Brookings, Or. 97415
Method of sealing strata off	[Signed] Hugh Malay
Vas well gravel packed? ☐ Yes ☒ No Size of gravel:	(Water Well Contractor)
9	Contractor's License No. 724 Date 28 19 21