RECEIVED

CURR 50874

CURR

STATE OF OREGON

JUN 1-9 2002

50874

WELL I.D. # { START CARD #_

WATER SUPPLY WELL REPORT RESOURCES DEPT.		WELL I.D. # L	. <u>511177</u> # <u>14783</u> 2		
(as required by ORS 537.765) SALEM, OREGON Instructions for completing this report are on the last page of this form.		SIAKI CARD	# <u>/4/03</u>		
(1) LAND OWNER Well Number 830 Name Dept. Of Parks + Recreation (Curry County)	(9) LOCATION OF WELL by legal description: County Latitude Longitude				
Address PO BGx 1345	County Latitude Longitude Township 33 N or S Range 5 E or W WM.				
City Port Orford State OR Zip 97465	Section 25 NE 1/4 SE 1/4				
(2) TYPE OF WORK	Tax Lot 2400 LotBlockSubdivision				
New Well Deepening Alteration (repair/recondition) Abandonment	Street Address of Well (or nearest address)				
(3) DRILL METHOD: RECEIVED	Humbing Mtm.				
X Rotary Air X Rotary Mud ☐ Cable ☐ Auger	(10) STATIC WATER LEVEL: ft. below land surface. Date			1,00/0-	
Other			_	117/02	
(4) PROPOSED USE: ***********************************	Artesian pressurelb. per square inchlb. Datelt.				
☐ Thermal ☐ Injection ☐ Livestock ☐ Other SALE MICKEGON	' (11) WATER BEARII 	NG ZONES:			
(5) BORE HOLE CONSTRUCTION:	Depth at which water was	s first found			
Special Construction approval Yes No Depth of Completed Well	From	To	Estimated Flow Rate	SWL	
Explosives used Yes No TypeAmount	3	15	20	2'	
HOLE SEAL	23	166	+1-5	5'	
Diameter From To Material From To Sacks or pounds		7 & Y			
6" 19 166 Jentonite 0 19 31 5X					
	(12) WELL LOG:				
How was seal placed: Method $\Box A \Box B \Box C \Box D \Box E$	Ground	d Elevation/	- 100'		
Mother Poured From Surface					
Backfill placed fromft. toft. Material	Materia	al	From To	SWL	
Gravel placed fromft. toft. Size of gravel	TOPSOIL		0 /		
(6) CASING/LINER:	Clay w/ Gravel CPS-Fine / 3 2'				
Diameter From To Gauge Steel Plastic Welded Threaded Casing: 6" +1"6" 239" 250 🖸 🖂 🖂	Grave (CRS-Fine W/ Clay Stone 3 /3) 4 Sandstone Fractured Graybin				
	Gravel (RS Fine W/ Fractured 13 15				
	Clayfore + conditions + orang clay				
	Sanctistone Gruy 15 19				
Liner:	Claystone Brna	Com W Bunt	19 22		
	Jandstone 61	reli	22 23	5	
Drive Shoe used	ClayStone Grey 23 25				
(7) PERFORATIONS/SCREENS:	5 and store 6		25 29		
Perforations Method	Sandofore W/C	laystone &	29 38		
☐ Screens Type Material	Quartz lens	ses Gray			
Slot Tele/pipe	Chujstone Wison	ndstone + Qu		1	
From To size Number Diameter size Casing Liner	Songstone WIC	1//	505 Gray -13 76		
	Sondstone gray w	, , , , , , , , , , , , , , , , , , ,	Quartz 76 92		
	Green Chistal Brush + 158 166				
	5 and stone	,	130 166		
		(-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	pleted 6/17/02		
(8) WELL TESTS: Minimum testing time is 1 hour Flowing	(unbonded) Water Well Co				
X Pump ☐ Bailer ☐ Air ☐ Artesian				adon.	
Yield gal/min Drawdown Drill stem at Time	I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction				
/2 //5 1 hr.	standards. Materials used and information reported above are true to the best of my knowledge and belief.				
4.3 Actual Production	Rhowledge and belief.	/	WWC Number 175	9	
	Signed	Elson	Date	9/02	
Temperature of water Depth Artesian Flow Found	(bonded) Water Well Cons	structor Cer sti cati	on:		
Was a water analysis done? Yes By whom But	I accept responsibility for the construction, alteration, or abandonment work				
Did any strata contain water not suitable for intended use?	performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well				
☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other	construction standards. This report is true to the best of my knowledge and belief.				
Bendon Well & Septic Co., Inc.	Depth of strata: Rendon Well & Septic Co., Inc. Signed On Male & Make Date (6/18/02)				
RSUODII MAGINAL AND	Sigileu		Date _6/4	7/06	
ORIGINAL – WATER RESOURCES DEPARTMENT FIRST	COPY - CONSTRUCT	OR SECONE	O COPY - CUSTOMER		