STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

CURR 52371

9/7/2012

WELL I.D. LABEL# L
START CARD # 1
ORIGINAL LOG # 0

			Page 1 of 1
_	109138		-
	1017632		
	CURRY	261	•

(1) LAND OWNER Owner Well I.D. 1423		
First Name C/O MAC Last Name MCDONALD	(9) LOCATION OF WELL (legal description)	
Company SAUNDERS CREEK HOMEOWNERS COOPERATIVE	County CURRY Twp 36.00 S N/S Range 14.00	W F/WWM
Address 95691 SAUNDERS CREEK ROAD	Sec 21 SW 1/4 of the NW 1/4 Tax Lot 22	
City GOLD BEACH State OR Zip 97444	Toy Man Nymbon	
(2) TYPE OF WORK New Well Deepening Conversion	Tax Map Number Lot Lat ' " or Long ' " or	DMS or DD
Alteration (complete 2a & 10) Abandonment(complete 5a)	Lat oi	_ DMS OF DD
(2a) PRE-ALTERATION	Street address of well Nearest address	_ DMS or DD
Dia + From To Gauge Stl Plstc Wld Thrd Casing: 12 X 1.33 88 .250 ♠ ✓ X □		
	95691 SAUNDERS CREEK ROAD, GOLD BEACH	
Material From To Amt sacks/lbs		
Seal: (3) DRILL METHOD	(10) STATIC WATER LEVEL	
Rotary Air Rotary Mud Cable Auger Cable Mud	Date SWL(psi) +	SWL(ft)
	Existing Well / Pre-Alteration 9/6/2012	28
Reverse Rotary X Other 5T SMEAL	Completed Well 9/6/2012	28
(4) PROPOSED USE Domestic Irrigation X Community	Flowing Artesian? Dry Hole?	
	WATER BEARING ZONES Depth water was first found	28.00
Thermal Injection Other	· ·	
	SWL Date From To Est Flow SWL(psi)	+ SWL(ft)
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy)	9/6/2012 28 88 40	28
Depth of Completed Well 88.00 ft.		
BORE HOLE SEAL sacks/		
Dia From To Material From To Amt 1bs		
12 0 88		
	(11) WELL LOG Ground Elevation 150.00	
How was seal placed: Method A B C D E		
Other PREVIOUSLY INSTALL	Material From Well originally drilled 9/21/1965. 0	To 88
Backfill placed from ft. Material	Curry 000261 by Mohr Well Drilling 0	88
	Well 84' @ start. Brushed casing and 0	88
Filter pack from 33 ft. to 88 ft. Material SAND Size 6/9	sand pumped scale, sand & silt to 88'	88
Explosives used: Yes Type Amount Amount	Installed 8" PVC screen from 58'-88' 0	88
(5a) ABANDONMENT USING UNHYDRATED BENTONITE	and 8" solid pvc to surface. Hole was 0	88
Proposed Amount Actual Amount	sand packed between 12" & 8" w/6-9sand 0	88
(6) CASING/LINER	Hole was chlorinated & backflushed 0	88
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	w/500 gal of water. Well was test pumped 0	88
	Steel casing, perforations, and seal 0	88
● 12 X 1.3 88 .250 ● X	installed by original driller and not 0	88
	altered by Bandon Well & Pump 0	88
Shoe Inside Outside Other Location of shoe(s)		
Temp casing Yes Dia From To		
(7) PERFORATIONS/SCREENS Perforations Method Torch(Previously Ins		
Screens Type Johnson/Lazer Cut Material PVC	D. Complete 0/c/2012	
Perf/ Casing/ Screen Scrn/slot Slot # of Tele/	Date Started 9/6/2012 Complete 9/6/2012	
Screen Liner Dia From To width length slots pipe size	(unbonded) Water Well Constructor Certification	
Perf Casing 12 60 88 .125 0 0 12	I certify that the work I performed on the construction, deepeni	ing, alteration, or
Screen Casing 8 58 88 .05 8	abandonment of this well is in compliance with Oregon wa	
	construction standards. Materials used and information reported	above are true to
	the best of my knowledge and belief.	
	License Number Date	
(8) WELL TESTS: Minimum testing time is 1 hour	Siana I	
Pump	Signed	
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	(bonded) Water Well Constructor Certification	
30 35 80 1	I accept responsibility for the construction, deepening, alteration	or abandanman
	work performed on this well during the construction dates reported	
	performed during this time is in compliance with Oregon wa	
Temperature 52 °F Lab analysis Yes By	construction standards. This report is true to the best of my knowledge.	
	License Number 1493 Date 9/7/2012	
Water quality concerns? Yes (describe below) TDS amount From To Description Amount Units	1495 Date 9/1/2012	
	Signed JAMES A MACK SR (E-filed)	
	Contact Info (optional) BANDON WELL & PUMP COMPANY ((541) 347-7867
	· · · · · · · · · · · · · · · · · · ·	