STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210) **CURR 52469**

12/25/2013

WELL I.D. LABEL# L 11
START CARD # 10
ORIGINAL LOG #

		rage 1 01 1
L	110222	
	1021884	

(1) LAND OWNER Owner Well I.D. 1478		
First Name JACK Last Name LEWIS	(9) LOCATION OF WELL (legal description)	
Company		
Address PO BOX 934	County CURRY Twp 32.00 S N/S Range 15.00 W	_ E/W WM
City PORT ORFORD State OR Zip 97465	Sec <u>29 SE</u> 1/4 of the <u>SE</u> 1/4 Tax Lot <u>1200</u>	
· ·	Tax Map Number Lot Date Lot Date	
	Lat' " or D	MS or DD
Alteration (complete 2a & 10) Abandonment(complete 5a) (2a) PRE-ALTERATION	Long or D	MS or DD
Dia + From To Gauge Stl Plstc Wld Thrd	Street address of well Nearest address	
Casing: Casing	42764 PORT ORFORD LOOP, PORT ORFORD	
Material From To Amt sacks/lbs		
Seal:		
(3) DRILL METHOD	(10) STATIC WATER LEVEL	
Rotary Air Rotary Mud Cable Auger Cable Mud	L ` '	WL(ft)
	Existing Well / Pre-Alteration	
Reverse Rotary Other	Completed Well 12/24/2013	33
(4) PROPOSED USE	Flowing Artesian? Dry Hole?	
Industrial/ Commercial Livestock Dewatering		
	WATER BEARING ZONES Depth water was first found 33.00	
Thermal Injection Other	SWL Date From To Est Flow SWL(psi) + 5	SWL(ft)
(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy)	12/24/2013 33 60 25	33
Depth of Completed Well 60.33 ft.	12/24/2013 33 00 23	33
BORE HOLE SEAL sacks/	 	
Dia From To Material From To Amt lbs		
10 0 61 Bentonite 0 32 22 S		
10 0 01 Bentonite 0 32 22 3		
	(11) WELL LOG Ground Elevation 150.00	
How was seal placed: Method A B C D E		To
X Other POUR FROM SURFACE	Topsoil 0	1
D. 16th 1 - 16	Clay brown 1	3
Backfill placed from ft. to ft. Material	Sand f-c brown 3	4
Filter pack from 32 ft. to 61 ft. Material SAND Size 10/20		6
Explosives used: Yes Type Amount	Saint Te Stange Stown	
		11
(5a) ABANDONMENT USING UNHYDRATED BENTONITE		
Proposed Amount Actual Amount	8.8.7	20
(6) CASING/LINER		
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	Gravel f-c w/sand & sandy clay tan orang 26 Gravel f-m w/sand c-f orange brown 29	29 35
● ○ 6 X 1.5 4 .250 ● ○ □ □ □	Gravel f-m w/sand c-f orange brown 29 Gravel m-f-c w/sand c-f orange brown 35	55
● 5 🛛 1 55.33 Sdr26 🔘 ● 🗶	Gravel f-c w/sand c-f brown orange 55	59
	gravel f-m w/sand c-f & sandy clay tan 59	61
	Set screen 23-28 no water (removed) 59	61
	Set sereen 23-28 no water (removed)	01
Shoe Inside Outside Other Location of shoe(s)		
(7) PERFORATIONS/SCREENS		
Perforations Method	 	
Screens Type Johnson V-Wire Material Stainless Steel	Date Started 12/23/2013 Complete 12/24/2013	
Perf/ Casing/ Screen Scrn/slot Slot # of Tele/	(I I I I I I I I I I I I I I I I I I I	
Screen Liner Dia From To width length slots pipe size	(unbonded) Water Well Constructor Certification	
Screen Casing 5 55.33 60.33 .021 5	I certify that the work I performed on the construction, deepening, a	
	abandonment of this well is in compliance with Oregon water s	
	construction standards. Materials used and information reported above the best of my knowledge and belief.	e are true to
	, , ,	
	License Number Date	
(8) WELL TESTS: Minimum testing time is 1 hour	,	
Pump Bailer () Air Flowing Artesian	Signed	
	(bonded) Water Well Constructor Certification	
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)		
25 60 1	I accept responsibility for the construction, deepening, alteration, or a	
	work performed on this well during the construction dates reported abo	
	performed during this time is in compliance with Oregon water	
Temperature 53 °F Lab analysis X Yes By Bandon Well & Pump Co.	construction standards. This report is true to the best of my knowledge	and bellet.
Water quality concerns? Yes (describe below) TDS amount	License Number 1493 Date 12/25/2013	
From To Description Amount Units		
	Signed JAMES A MACK SR (E-filed)	
	Contact Info (optional) Bandon Well & Pump Company (541) 347-786	7