The original and first copy

## WATER WELL REPORT

of this report are to be filed with the

STATE ENGINEER, SALEM, OREACT 97310 L 28 1970 (Do not write above this line)

8P\*45656-119

STATE ENGINEER, SALEM, ORFIGN 97310 28 1970 (Do not write ab	or print) State Permit No.
	ove this line)
(1) OWNER: SALEM. OREGON	(10) LOCATION OF WELL:
	County Carry Driller's well number
Name Rogge The Sales	7, T
Address P.O. 608 Bandon Oregon	E 3 NW4 Section 9 T. 32 5 R. 15 W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well   Deepening □ Reconditioning □ Abandon □	## ##
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 38 ft.
Rotary Driven Domestic M Industrial Municipal Domestic	Static level 33 ft. below land surface. Date 7-24-7
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing
6." Diam from O ft. to 64 ft. Gage 250	Depth drilled $\langle G \rangle$ ft. Depth of completed well $\langle G \rangle$ ft.
"Diam. from	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated?   Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
	Carlotte Car
Size of perforations in. by in.	Bentonite slurry used in drilling of first 30 feet.
perforations fromft. toft.	TEN INCH WELL PORE TO 18 feet
perforations fromft. toft.	Sandy soil gray 0 1
perforations from ft. to ft.	Sand packed Medium Brown 1 3
(7) SCREENS: Well screen installed?   Yes No	Sand Course TAN 3 27
Manufacturer's Name	GRAVEL FINE 27 30
Type Model No.	CEMENTED GRAVEU BROWN 30 38
Diam. Slot size Set from ft. to ft.	DIRTY GRAVEL TOTEDIUM 38 43
Diam. Slot size Set from ft. to ft.	Clay & FINE GRAVEL BROWN 43 59
(8) WELL TESTS: Drawdown is amount water level is	FINE SAND & GRAVEL " 59 67
lowered below static level	Clay & FINE GRAVEL 64 60
Was a pump test made?   Yes No If yes, by whom?	BRUWN
Yield: gal./min. with ft. drawdown after hrs.	- may the the property of the state of the s
" " " " " " " " " " " " " " " " " " " "	The second secon
n n n	- Company of the Comp
Bailer test / O gal./min. with TOTAL drawdown after / Krs.	
Artesian flow g.p.m.	
perature of water 52 Depth artesian flow encountered ft.	Work started July 221970 Completed July 241970
(9) CONSTRUCTION:	Date well drilling machine moved off of well July 24 1970
Well seal-Material used Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Andrew W Millerate 7-24, 1970
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's vicense No
Brand name of bentonite NATIONAC BAROID	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	_
of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used?   Yes No Plugs Size: location ft.	Name George PMIller
Did any strata contain unusable water?   Yes  No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address / 30x 30x / Sagados 01 e
Method of sealing strata off	[Signed] Deorge To Miller
Was well gravel packed?  Yes W No Size of gravel:	Contractor's License No. 2 2 Date 162 12 2 7 18
Gravel placed from ft. to ft.	Contractor's License No.