

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy of this report  
are to be filed with the

WATER RESOURCES DEPARTMENT,  
SALEM, OREGON 97310  
within 30 days from the date  
of well completion.

WATER WELL REPORT  
RECEIVED  
STATE OF OREGON  
(Please type or print)  
AUG 22 1978  
(Do not write above this line)

CURR 778  
000774  
State Well No. 415/136-159c  
State Permit No.

(1) OWNER:

Name Pacific Bulb Growers Test Station  
Address Box AB  
Brookings Oregon 97415

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary  Driven   
Cable  Jetted   
Dug  Bored   
Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

(4) PROPOSED USE (check):

(5) CASING INSTALLED:

6" Diam. from 0 ft. to 46'-7" ft. Gage 250  
" Diam. from ft. to ft. Gage  
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated?  Yes  No.  
Type of perforator used Torch  
Size of perforations 1/4 in. by 6 in.  
29 perforations from 33 ft. to 45 1/2 ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

(7) SCREENS:

Well screen installed?  Yes  No  
Manufacturer's Name  
Type Model No.  
Diam. Slot size Set from ft. to ft.  
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level  
Was a pump test made?  Yes  No If yes, by whom?  
Yield: gal./min. with ft. drawdown after hrs.  
" " " "  
" " " "  
Bailer test 20 gal./min. with 3 ft. drawdown after 1 hrs.  
Artesian flow g.p.m.  
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used No additional seal installed  
Well sealed from land surface to ft.  
Diameter of well bore to bottom of seal in.  
Diameter of well bore below seal in.  
Number of sacks of cement used in well seal sacks  
How was cement grout placed?  
Was a drive shoe used?  Yes  No Plugs Size: location ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel:  
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Curry Driller's well number  
NE 1/4 NE 1/4 Section 15 T41s R. 13W W.M.  
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 31'-10" ft.  
Static level 31'-10" ft. below land surface. Date 8-8-78  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0  
Depth drilled 46 1/2 ft. Depth of completed well 46 1/2 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Original			
twelve inch perforated casing	6	40'-10"	
Six inch perforated casing installed inside of twelve inch casing and deepened.			
Gravel brown	40	45 1/2	
Serpentine blue	45 1/2	47 1/2	

Work started 8-7 19 78 Completed 8-8 1978  
Date well drilling machine moved off of well 8-8 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Andrew W. Miller Date 8-20, 1978  
(Drilling Machine Operator)  
Drilling Machine Operator's License No. 469

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Bill Miller Well Drilling  
(Person, firm or corporation) (Type or print)  
Address Rt. 1, Box 1115 Bandon, Oregon 97411  
[Signed] Andrew W. Miller  
(Water Well Contractor)  
Contractor's License No. 600 Date 8-20, 1978