NOTICE TO WATER WELL CONTRACTOR_
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGONAUG1 41975

State Well No. 419/1314-15

(1) OWNER:	(10) LOCATION OF WELL:
Name Norman Yock (Ore. Propagating C.)	County Curry Driller's well number
Address Route 1, Box 52E	NW 1/4 NW 1/4 Section 15 T.41s R. 13w W.M.
Brookings Oregon 97415	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check): REPLACEMENT	nu nu
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1
Cable X Jetted Domestic Industrial Maincipal	Static level 25'-4" ft. below land surface. Date 7-28-75
Dug ☐ Bored ☐ Irrigation ☒ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: 8 " Diam. from + 1 ft. to 27!-8!! ft. Gage • 250 6 " Diam. from ft. to 40!-3!! ft. Gage • 250 " Diam. from ft. to ft. Gage • 250 PERFORATIONS: Perforated? Yes No.	Depth drilled $40\frac{1}{2}$ ft. Depth of completed well 40^{1} — 3^{11} ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Well # 4
perforations from ft. to ft.	Soil-clay dark brown 0 2
perforations from ft. to ft.	Clay brown 2 10
perforations from ft. to ft.	Sandy clay brown 10 17
(W) CONTRACTO	Clay & gravel brown 17 21
(7) SCREENS: Well screen installed? K Yes \(\subseteq \) No	Sand coarse with gravel 21 25
Manufacturer's Name Houston	Gravel medium with sand 25 36 8"
Type Stainless steel Model No. telescope	Serpentine rock blue 36'-8" 40'-3"
Diam. 8 Slot size .025 Set from 26! ft. to 32! ft. Diam. 8 Slot size .020 Set from 32 ft. to 37! 3!! ft.	
DiamO Slot size set from it. to it.	A77 was was was to keep of top of paging
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	All measurements taken at too of casing which is 12 inches above gracing line.
Was a pump test made? ☐ Yes 🖔 No If yes, by whom?	WILCH IS IN THOMES above gradule I he
Yield: gal./min. with ft. drawdown after hrs.	
	enter
	- 78.1
Bailer test 30 gal./min. with 2 ft. drawdown after $3\frac{1}{2}$ hrs.	
Artesian flow g.p.m.	July Thely
nperature of water 52 Depth artesian flow encountered ft.	Work started August 24 1975 Completed August 28 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well August 28 1975
Well seal—Material used Bentonite & cement	Drilling Machine Operator's Certification:
Well sealed from land surface to1.8 ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of seal12 in.	best knowledge and belief.
Diameter of well bore below seal8 in.	[Signed] Malle U. T. Jelle 1 Date 8-11, 1975.
Number of sacks of cement used in well seal $2\frac{1}{2}$ sacks	Orilling Machine Operator's License No. 469
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.
Brand name of bentonite Yellowstone	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water 100 lb./50gal. lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? 🗌 Yes 况 No Plugs Size: location ft.	Name George R. Miller & Son
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Route 1, Box 770 Bandon, Oregon 97411
Method of sealing strata off	[Signed] Andrew With Leller
Was well gravel packed? ☐ Yes 🖔 No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 600 Date August 11 , 1975