WATER WELL REPORT STATE OF OREGON

CURR 000807

RECEIVED
AUG3 1 1982
State Well No.

	1 LEPH (UMBA) IN B
1) OWNER:	(10) LOCATION OF WELL:
Name Norm Yock	County Curry Driller's well number
Address Rt. 1, Box 52 E	NE. ¼ NE. ¼ Section 16 T. 41s R. 13w W.M.
State Ore.	Tax Lot # Lot Blk Subdivision
	Address at well location: Same
2) TYPE OF WORK (check):	
Deepening Reconditioning Abandon	(11) WATER LEVEL: Completed well.
f abandonment, describe material and procedure in Item 12.	101-48
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft. Static level 10'-4" ft. below land surface. Date 8-24-82
Rotary Air Driven Domestic Industrial Municipal	Artesian pressure lbs. per square inch. Date
totan Mud □ Dug □ Irrigation ★ Test Well □ Other □ Withdrawal □ Reinjection □	
	(12) WELL LOG: Diameter of well below casing
5) CASING INSTALLED: Steel Plastic Under Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show
Threaded Welded 19'-10'' Gauge .250	thickness and nature of each stratum and aquifer penetrated, with at least one entry
6." Diam. from	for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED: NO	MATERIAL From To SWL
:	MATERIAL From 10 SWL
	State well # 10
(6) PERFORATIONS: Perforated? Yes No	Otate Well # 10
Type of perforator used	Clay with bentonite brown 0 8
Size of perforations in. by in.	Concrete 8 12
perforations from ft. to ft.	Gravel coarse brown 12 24.5
perforations from ft. to ft. to ft.	Serpentine blue 24.5 27.5
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? X Yes \square No	
Manufacturer's Name Johnson	
Type Stainlss.steel	
Diam. 8 Slot Size • 016. Set from 1811. ft. to 247. ft.	
Diam. Slot Size Set from ft. to ft. to ft. to prawdown is amount water level is lowered	
(8) WELL TESTS: below static level below static level	
a pump test made? Yes X No If yes, by whom?	
Feld: gal./min. with ft. drawdown after hrs.	
II " " " "	
Air test gal./min. with drill stem at ft. hrs.	
Bailer test 30 gal/min. with 5 ft. drawdown after 1 hrs.	
esian flow g.p.m.	
Pemperature of water 52 Depth artesian flow encountered ft.	Work started 8-23 19 82 Completed 8-24 1982
(9) CONSTRUCTION: Special standards: Yes No 🗆	Date well drilling machine moved off of well 8-24 1982
Well seal—Material used Bentonite capped with cement	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used
Diameter of well bore to bottom of seal	and information reported above are true to me best knowledge and belief.
Diameter of well bore below seal	[Signed] W. William Machine Operator) Date
Number of sacks of cement used in well seal . 1	Drilling Machine Operator's License No
How was cement grout placed? 75 1b. bentonite used	Water Well Contractor's Certification:
pumped via tremie pipe	This well was drilled under my jurisdiction and this report is true to
Was pump installed? 1100	the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes No Plugs Size: location ft.	Name Bill Miller Well Drilling
Did any strata contain unusable water? Yes No Yes No	(Person, firm or corporation) (Type or print) Address Route 1, Box 1115, Bandon, Ore. 97411
Type of Water? depth of strata	D. A. Ilan B.
Method of sealing strata off	[Signed] (Maldelle (Wather Well Contractor)
Was well gravel packed? 🗆 Yes 🌶 No Size of gravel:	Contractor's License No. 600 Date 8-28 , 19.82
Gravel placed from	,