## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this pet CE Veager WELL REPORT are to be filed with the

WATER RESOURCES DEPARTMENT AUG 3 0 1977

STATE OF OREGON (Please type or print)

State Permit No. ....

?	R	,	,	,	0	0	0	8	1/	2	1,2		-1	1.
		State	e	V	Vell	N	о.		7	5/	(/)	W		Ψ

within 30 days from the date
of well completion!!/ATER RESOURCES DESPTITE above this line)

_	·	*	•	, C	1	UC	إيار	4	בו 1		-1	1	^
	Sta	ate	3	Well	l No		7	75/	//>	W			4
								ı					

SALEM, OREGON							
(1) OWNER:	(10) LOCATION OF WELL:						
Name Norm Yock Oregon Propagating	County Curry Driller's well number						
Address Route 1 Box 52E	14 14 Section 16 T. 41s R. 13w W.M.						
Brookings Oregon	Bearing and distance from section or subdivision corner						
(2) TYPE OF WORK (check):	565 feet south 1610 feet west of northeast						
New Well Deepening 🗆 Reconditioning 🗀 Abandon 🗀	corner of section 16						
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.						
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found $12\frac{1}{2}$ ft.						
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal	Static level $12\frac{1}{2}$ ft. below land surface. Date $8-15-77$						
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date						
8 "Diam from 4 2 ft. to 16'-8" ft. Gage 250 6 "Diam from 25'-8" ft. to 29'-1" ft. Gage 250 "Diam from from ft. to ft. Gage .250	(12) WELL LOG:  Depth drilled 29  ft. Depth of completed well 29  ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in						
PERFORATIONS: Perforated? Tyes No.	position of Static Water Level and indicate principal water-bearing strata.  MATERIAL From To SWL						
	Well number # 10						
	Crane construction completed with drilling rig.						
perforations from ft. to ft.	Clay soil dark brown 0 2						
perforations from ft. to ft.	Clay brown and blue 2 12						
	Gravel and sand 12 26						
(7) SCREENS: Well screen installed? Yes \( \subseteq \text{No} \)	Serpentine blue - 26 29						
Manufacturer's Name Rosco-moss gravel gaurd							
Type Louvered pipe Model No. pipe size Diam. Slot size 16!-8" set from 16!-8" ft. to 26!-8" ft.	All measurements taken at top of casing which						
Diam. Slot size 250 Set from ft. to ft. Diam. Slot size 250 Set from ft. to ft.	is 24 " above ground.						
Diam, Stot size Set from 1t. to 1t.	Could not bail test well because of exceptation						
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	10" of concrete placed at 12 feet, remainder of bore hole filled with a mixture of 50%						
Was a pump test made?   Yes No If yes, by whom?	hentonite and 50% native clay.						
gal./min. with ft. drawdown after hrs.							
W # #	· · · · · · · · · · · · · · · · · · ·						
n n n							
Bailer test NONE gal./min. with ft. drawdown after hrs.							
Artesian flow g.p.m.	MARKAN AND AND AND AND AND AND AND AND AND A						
perature of water 52 Depth artesian flow encountered ft.	Work started 8-15 1977 Completed 8-15 1977						
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8-15 1977						
Well seal—Material used Cement bentonite native clay	Drilling Machine Operator's Certification:						
Well sealed from land surface to12	This well was constructed under my direct supervision.  Materials used and information reported above are true to my						
Diameter of well bore to bottom of seal 3X6 in.	best knowledge and belief.						
Diameter of well bore below seal3X6 in.	[Signed] (Malling Machine Operator) Date 8-29 , 19.77						
Number of sacks of cement used in well seal	Drilling Machine Operator's License No. 469						
How was cement grout placed?							
	Water Well Contractor's Certification:						
	This well was drilled under my jurisdiction and this report is						
Was a drive shoe used?   Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.  Bill Miller Well Orilling						
Did any strata contain unusable water?  Ves No	Name (Person, firm or corporation) (Type or print)						
Type of water? depth of strata	Address Route 1, Box 1115 Bandon, Ore 97411						
Method of sealing strata off	A. a. man Colon illa						
Was well gravel packed? Yes □ No Size of gravel: 11/2	[Signed] (Water Well Contractor)						
Gravel placed from $12$ ft. to $26\frac{1}{2}$ ft.	Contractor's License No. 600 Date 8-29 19.77						
The state of the s	,						