NOTICE TO WATER WELL CONTRACTOR The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPRECEIVED

STATE OF OREGON AUG 1 5 1975 State

(Please type or print)

(Please type or print)
(Do not write above WATER RESOURCES DEP Permit No SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name Norman Yock (Ore. Propagating Co.)	County Curry Driller's well number
Address Route 1, Box 52E	NE 14 NE 14 Section 16 T. 41s R. 13w W.M.
Brookings, Oregon 97415	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check): Replacement	
New Well Deepening Reconditioning Abandon	- مو - الله الله الله الله الله الله الله ال
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 18 ft.
Sima	Static level 171_4" ft. below land surface. Date 8_6_75
Rotary Driven DCable Demostic Driven Dug Bored DCAD Irrigation DCAD Test Well Dother	Artesian pressure lbs. per square inch. Date
Dug Dotet Infanton & 155	Altesial pressure
CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well below casing
8 " Diam. from + 2 ft. to 20!-6" ft. Gage 250	Depth drilled 33 ft. Depth of completed well 33 ft.
6 " Diam. from30 ft. to33 ft. Gage250	Formation: Describe color, texture, grain size and structure of materials;
ft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes You	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
	Well # 3
	Well #)
perforations from ft. to ft ft ft.	Clay soil dark brown 0 4
perforations from ft. to ft.	Clay with gravel brown 4 13
	Gravel brown 13 $28\frac{1}{2}$
(7) SCREENS: Well screen installed? Yes \(\square\) No	Serpentine blue $28\frac{1}{2}$ 33
Manufacturer's Name Houston	
Type Stainless steel Model No. telescope	All measurements taken from top of casing
Diam. 8 Slot size025 Set from 19!-3!! ft. to .24!-7!! ft. Diam. 8 Slot size025 Set from 24!-7!! ft. to 30 ft.	
Diam. Slot size Set from 11 to 2	which is 24 inches above ground line
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes K No If yes, by whom?	
Yield: gal./min. with ft. drawdown after nrs.	
	1.
Bailer test 30 gal./min. with 3 ft. drawdown after $3\frac{1}{2}$ hrs.	
Artesian flow g.p.m.	A LIB TO THE REAL OF STREET
nperature of water 52 Depth artesian flow encountered ft.	Work started August 4 1975 Completed August 6 1975
(9) CONSTRUCTION:	Date well drilling machine moved off of well August 6 1975
Well seal-Material used Bentonite & cement	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief
Diameter of well bore below seal	[Signed]
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No
Number of sacks of bentonite used in well seal sacks Brand name of bentonite Yellowstone	
	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water 100 lb./50 gal. lbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes ♣ No Plugs Size: location	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name George R. Miller & Son (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address Route 1, Box 770 Bandon, Ore. 97411
Method of sealing strata off	Ind. 1 10AM Ill.
Was well gravel packed? ☐ Yes 🛱 No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No600 Date August 11, 19.75
GLAYOL PLACEU LLVIII	