

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT  
SALEM, OREGON 97310  
within 30 days from the date of well completion.

WATER WELL REPORT  
**RECEIVED**  
STATE OF OREGON  
Please type (in full)

(Do not write above this line)  
AUG 23 1978

CURR 000820  
State Well No. 415/13w-1696  
State Permit No.

(1) OWNER:  
Name Norm Yock  
Address Route 1, Box 52E  
Brookings Oregon 97415

(2) TYPE OF WORK (check):  
New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):  
Rotary  Driven  Domestic  Industrial  Municipal   
Cable  Jetted  Irrigation  Test Well  Other   
Dug  Bored

CASING INSTALLED:  
8" Diam. from +2 ft. to 34'-10" ft. Gage .250  
6" Diam. from 32'-6" ft. to 35'-6" ft. Gage .250

PERFORATIONS:  
Type of perforator used Torch  
Size of perforations 1/4 in. by 12 in.  
25 perforations from 23'-10" ft. to 33'-10" ft.

(7) SCREENS:  
Well screen installed?  Yes  No  
Manufacturer's Name  
Type Model No.  
Diam. Slot size Set from ft. to ft.  
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:  
Drawdown is amount water level is lowered below static level  
Was a pump test made?  Yes  No If yes, by whom?  
Yield: gal./min. with ft. drawdown after hrs.  
Bailer test \*\*\*\*\* gal./min. with \*\*\* ft. drawdown after \*\*\*\*\* hrs.  
Artesian flow g.p.m.  
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:  
Well seal—Material used Bentonite, clay, concrete  
Well sealed from land surface to 12 ft.  
Diameter of well bore to bottom of seal 8 ft.  
Diameter of well bore below seal 8 in.  
Number of sacks of cement used in well seal 12" concrete sacks  
How was cement grout placed? grouted from surface

Was a drive shoe used?  Yes  No Plugs Size: location ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel:  
Gravel placed from ft. to ft.

WATER RESOURCES DEPARTMENT (10) LOCATION OF WELL:  
SALEM, OREGON County Curry Driller's well number

NW 1/4 NE 1/4 Section 16 T. 41s R. 13w W.M.  
Bearing and distance from section or subdivision corner  
215 feet south 1450 feet west of NE corner

(11) WATER LEVEL: Completed well.  
Depth at which water was first found 12'-6" ft.  
Static level 12'-6" ft. below land surface. Date 8-7-78  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 0  
Depth drilled 35 1/2 ft. Depth of completed well 35 1/2 ft.  
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Well No. 1			
State No. 8			
Application # G 7684			
Permit # G 7156			
Construction by crane and cable tool.			
Clay soil dark brown	0	2	
Clay brown	2	11	
Gravel & sand brown	11	32	
Serpentine blue	32	35 1/2	
No ball test due to excavation.			
All measurements taken at top of casing which is two feet above land surface.			

Work started 8-4 19 78 Completed 8-7 19 78  
Date well drilling machine moved off of well 8-8 19 78

Drilling Machine Operator's Certification:  
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.  
[Signed] Andrew Miller Date 8-20, 19 78  
(Drilling Machine Operator)  
Drilling Machine Operator's License No. 469

Water Well Contractor's Certification:  
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.  
Name Bill Miller Well Drilling  
(Person, firm or corporation) (Type or print)  
Address Route 1, Box 1115 Bandon, Oregon  
[Signed] Andrew Miller  
(Water Well Contractor)  
Contractor's License No. 600 Date 8-20, 19 78