NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

16 St

-	U	U	U		· /	*	ر			arg
					;					A
. L. YYT.	11 %	~_	4	41		13	Lo	_	16	

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

well#1

STATE OF OREGON 65376
(Please type or print) G-4148

State	Well No	41	/13	W	 16	#
		•				
State	Permit No) .			 	

(1) OWNER:	(11) WELL TESTS: Drawdown is amount we lowered below static levels.	iter level is
Name Norman Yock (Orogon Propagatin	Was a pump test made? Yes XNo If yes, by whom?	
Address Brookings, Oregon Co.	Yield: gal./min. with ft. drawdown	after hrs.
	2)	23
(2) LOCATION OF WELL:	21 21 21	22
County Curry Driller's well number	Bailer test 50 gal./min. with 11 ft. drawdow	n after 🛣 🔁 hrs.
Ne ¼ Ne ¼ Section 15 T. 41 S R. 13 W W.M.	Artesian flow g.p.m. Date	•
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis ma	ade? 🗌 Yes 🔲 No
Dearing and distance from section of subdivision corner	(12) WELL LOG: Diameter of well below case	ing
* ·	Depth drilled 39 ft. Depth of completed well	1 39 ft.
	Formation: Describe by color, character, size of material show thickness of aquiflers and the kind and nature of the stratum penetrated, with at least one entry for each characteristics.	e material in each
	on death percentaged, with at teast the entry for each class	mge of formation.
(3) TYPE OF WORK (check):	MATERIAL	FROM TO
ar-	Black Loam	0 3
	Light Brown Clay	3 10
andonment, describe material and procedure in Item 12.	Dark 2 "	10 16
(4) PROPOSED USE (check): (5) TYPE OF WELL:		16 19
Domestic Industrial Municipal Rotary Driven	Light river Gravel .	19 39
Cable ☐ Jetted ☐ Irrigation X Test Well ☐ Other ☐ Dug ☐ Bored ☐		
(6) CASING INSTALLED: Threaded □ Welded □ X		
8 " Diam. from	. b. dates	
" Diam. from ft. to ft. Gage		
(7) PERFORATIONS: Perforated? XYes \(\square\) No		
Type of perforator used Acetylene	CECEIVE	
Size of perforations 3/8 in. by 10 in.		
40 perforations from 25 ft. to 38 ft.	MAUG 1 2 1965	
perforations from ft. to ft.	STATE ENGINEER	
perforations fromft. toft.	SALEM CREGON	
perforations from ft. to ft.		
perforations from ft. to ft.		-
(8) SCREENS: Well screen installed? ☐ Yes X No		
Manufacturer's Name		
Model No.		
Slot size Set from ft. to ft.		
Dian. Slot size Set from ft, to ft,	Work started 6/21 19 65 Completed 6/2	
	Date well drilling machine moved off of well 6/2	2 <u>4 196</u> 5
(9) CONSTRUCTION:	(13) PUMP:	
Well seal—Material used in seal Puddled Clay	Manufacturer's Name	
Depth of sealft. Was a packer used?NO	Type:H.F	······································
Diameter of well bore to bottom of seal 12 in.		-
Were any loose strata cemented off? 🗌 Yes 🛣 No 💮 Depth	Water Well Contractor's Certification:	
Was a drive shoe used? X Yes \(\square\) No	This well was drilled under my jurisdiction an	d this report is
Was well gravel packed? Yes Mo Size of gravel:	true to the best of my knowledge and belief.	
Gravel placed from ft. to ft.	NAME SO. STATE VIRIC	ime Co
Did any strata contain unusuable water? 🗌 Yes 💃 No	(Person, firm or corporation) (Type	or print)
Type of water? depth of strata	Address Canaris 1755 C	OKE_
Method of sealing strata off	Drilling Machine Operator's License No. 3.8.7.	
(10) WATER LEVELS:	Detailed Specialist Structure 140.	***************************************
Static level 22 ft. below land surface Date 6/23	[Signed] Ofer U. Our	non
Artesian pressure lbs. per square inch Date	(Water Well Contractor) Contractor's License No 2.46 Date	
The state of the s	1 Contractor's License No. L. Lo. Date	19

(USE ADDITIONAL SHEETS IF NECESSARY)