NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPRECEIVED

STATE OF OREGON AUGS 1973

State Well No. 415

(Please type or print)

(Do not write above this SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name Norman Yock (Oregon Propagating Company)	County Curry Driller's well nu		
Address Route 1, Box 52 E Brookings, Oregon	NE 14 NE 14 Section 16 T. 41s	R. 13w	W.M.
	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	27	ft.
Rotary Driven Domestic Industrial Municipal	Static level 26'-10" ft. below land s	surface. Date 7-31.	_74
Cable M Jetted D Domestic D Industrial D Mannespar			<u> </u>
Dug	Artesian pressure Ibs. per squar	e men. Date	
8 " Diam. from + 30 inft. to 28! -5" ft. Gage	(12) WELL LOG: Diameter of well below casing		
6 "Diam. from 38'-4" ft. to 41'-1" ft. Gage 250	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
PERFORATIONS: Perforated?   Yes No.  Type of perforator used	MATERIAL		SWL
Size of perforations in. by in.	-		
perforations from ft. to ft.	Clay soil dark brown	0 5 1/2	
perforations fromft. toft.	Clay hard brown sticky	5블 17블	
perforations from ft. to ft.	Gravel and sand gray	17를 37를	
	Clay brown	37 <del>½</del> 38½	
(7) SCREENS: Well screen installed? Yes \( \subseteq \) No	Serpentine rock blue	38출 41출	
Manufacturer's Name Johnson toloscope			<del></del> -
Type Stainless steel Model No. telescope	All formation measurements t	1 1	<del></del>
Diam. 8 Slot size • 025 Set from 27!—4" ft. to 33!—1" ft.  Diam. 8 Slot size • 020 Set from 33!—1" ft. to 38!—4" ft.	top of casing which is 30 inc	hes above	
Diam. Slot size • OSO Set from Set from It. to Set It.	ground line.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made?   Yes No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
Bailer test 30 gal./min. with 2 ft. drawdown after 1 hrs.		<u> </u>	
Artesian flow g.p.m.		<u> </u>	
perature of water 52 Depth artesian flow encountered ft.	Work started July 26 19 74 Complet		19 74
(9) CONSTRUCTION:	Date well drilling machine moved off of well	July 31	19 74
Well seal—Material used Bentonite & cement	Drilling Machine Operator's Certification:	<b>:</b>	
18	This well was constructed under my	direct supervi	sion.
Well sealed from land surface toft.  Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above are true to	o my
Diameter of well bore below seal		Date July 31., 1	19.74.
Number of sacks of cement used in well seal	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal1sacks	Drilling Machine Operator's License No.	469	
Brand name of bentonite Yellowstone	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons		liation and this war	ort ic
of water 100 1b./50 gal. lbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and be		OT 112
Was a drive shoe used?   Yes No Plugs Size: location ft.	Name George R. Miller & Son (Person, firm or corporation)	(Type or print)	
Did any strata contain unusable water?   Yes  No	_		
Type of water? depth of strata	Address Route 1, Box 770 Banc	ion Oregon 974	¥1.1
Method of sealing strata off	[Signed] - Jeorge B	Weller	
Was well gravel packed?   Yes K No Size of gravel:	(Water Well Cont		
	Contractoria License No. 322 Date	J11757 31	1074