

STATE OF OREGON
WATER WELL REPORT
(as required by ORS 537.765)

RECEIVED

OCT 17 1985

CURR
841

000841

415/13 W-22 AN

PLEASE TYPE or PRINT IN INK

(for official use only)

(1) OWNER:

Name HASTINGS INC.
Address 15342 OCEAN VIEW
City BROOKINGS State ORE

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air ☒ Driven ☐ Domestic ☐ Industrial ☐ Municipal ☐
Rotary Mud ☐ Dug ☐ Irrigation ☒ Thermal: ☐ Withdrawal ☐ ReInjection ☐
Cable ☐ Bored ☐ Other: ☐ Piezometric ☐ Grounding ☐ Test ☐

(4) PROPOSED USE (check):

(5) CASING INSTALLED:

Steel ☒ Plastic ☐
Threaded ☐ Welded ☒
6" Diam. from +2 ft. to 18 ft. Gauge 250
" Diam. from ft. to ft. Gauge

LINER INSTALLED:

Steel ☐ Plastic ☐
Threaded ☐ Welded ☐
" Diam. from ft. to ft. Gauge

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot Size Set from ft. to ft.
Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Id: gal./min. with ft. drawdown after hrs.
Air test 1 gal./min. with drill stem at 60 ft. 1 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 51° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Special standards: Yes ☐ No ☒
Well seal—Material used Cement
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Amount of sealing material 6 sacks ☒ pounds ☐
How was cement grout placed? pumped
Was pump installed? No Type HP Depth ft.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of Water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel: ft.
Gravel placed from ft. to ft.

(10) LOCATION OF WELL by legal description:

County CURRY NE 1/4 NE 1/4 of Section 22 of
Township 41s Range 13 WM.
(Township is North or South) (Range is East or West)
Tax Lot 500 Lot Block Subdivision
MAILING ADDRESS OF WELL (or nearest address)
Well #1

(11) WATER LEVEL of COMPLETED WELL:

Depth at which water was first found 39 ft.
Static level 36 ft. below land surface. Date 10-10-85
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 60 ft. Depth of completed well 60 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
TOP SOIL	0	9	
BROWN CLAY-some SMALL GRAVEL	9	39	36
BROWN CLAY-SMALL TO medium GRAVEL	39	56	
SHALE	56	60	
AQUIFER	38	39	19pm

RECEIVED

OCT 15 1985

WM. DIST. 14
GRANTS PASS, ORE.

Date work started 10-10-85 /completed 10-10-85
Date well drilling machine moved off of well 10-10 1985

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] MIKE PIERCE Date 10-10, 1985

(bonded) Water Well Constructor Certification:

Bond 2394665 Issued by: WESTERN SURETY
(number) (Surety Company Name)
On behalf of PAQUIN DRILLING
(type or print name of Water Well Constructor)

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:

(Signed) Bob Quinn
(Water Well Constructor)
(Dated) 10-15-85

NOTICE TO WATER WELL CONSTRUCTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

SP*46866-690