NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be

WATER WELL REPORCEIVED

315 15W-32ac

of this report are to be		L
filed with the	TO OREGON-	State Well No. 313
	97810 (Please type or print) EC3 1974 (Do not write above this half ENGINEER	
STATE ENGINEER, SALEM, OREGON	(Please type or print)	
within 30 days from the date	STATE ENGINEED	State Permit No
of well completion.	(Do not write above this line). LINGHYCEIX	-

(1) OWNER: CURR 9999	SALEM, ORECOM		
(1) OWNER:	(10) LOCATION OF WELL:		
	County Curry Driller's well number		
Name Reynold Rundberg	_ 		
Address Box 226 Sixes, Ore. 97476			
(0) TYPE OF WORK (about).	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 20 ft.		
Rotary Driven Domestic Industrial Municipal D	Static level 17½ ft. below land surface. Date 11-25-74		
Cable	Artesian pressure lbs. per square inch. Date		
	Theodal product		
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing		
6 "Diam. from 0 ft. to 841-211 ft. Gage 250	Depth drilled 92 \frac{1}{2} ft. Depth of completed well 92 \frac{1}{2} ft.		
5 "Diam. from 81'-3" ft. to 83'-3" ft. Gage •250	Formation: Describe color, texture, grain size and structure of materials;		
ft. Gage ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,		
DEDEOD A MIONG.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
PERFORATIONS: Perforated? Yes XX No.			
Type of perforator used			
Size of perforations in. by in.	Sand fill 0 2		
perforations from ft. to ft.	Clay soil black 2 3		
perforations from ft. to ft.	Danky Cray gray		
perforations from ft. to ft.			
(7) SCREENS: Well screen installed? Yes No	CALLY TAILY DAKE NATION NATIONAL NATION		
Manufacturer's Name Johnson	70010, 0000 00011 121 121		
Type Stainless steel Model No. telescope	Sand fine tight with fine gravel and clay lumps light blue30 40		
Diam. 6. Slot size .008. Set from 83!-3! ft. to 92!-4! ft.	Sand medium brown &fine gravel 40 45		
Diam. Slot size Set from ft. to ft.	Sand med. brown 45 47		
	Sand fine blue with wood 47 90		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Gravel medium with shell 90 92		
Was a pump test made? [] Yes [No If yes, by whom?	Claystone blue-grav 92 92 4		
Yield: gal./min. with ft. drawdown after hrs.			
" " " "			
Bailer test 30 gal./min. with 20 ft. drawdown after 1 hrs.			
Artesian flow g.p.m.			
perature of water 52 Depth artesian flow encountered ft.	Work started NOV. 19 1974 Completed NOV. 25 1974		
(9) CONSTRUCTION:	Date well drilling machine moved off of well New. 25 1974		
	Drilling Machine Operator's Certification:		
Well sealed from land surface to 20 ft.	This well was constructed under my direct supervision.		
. 10	Materials used and information reported above are true to my best knowledge and belief		
Diameter of well bore to bottom of seal	Made and KAS Illed 10 2 10 71		
Number of sacks of cement used in well seal	(Drilling Machine Operator)		
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No. 1469		
Brand name of bentonite Yellowstone			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water 100 lb. / 50 gal. lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the pest of my knowledge and belief		
Was a drive shoe used? Yes No Plugs Size: location ft.	The same of the same of the same		
Did any strata contain unusable water? Yes No	Name (Person, item or corporation) (Type or print)		
Type of water? depth of strata	Address Route, 1. Box 770 Bandon, Oregon		
Method of sealing strata off	Hand A Welle		
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contractor)		
	Contractor's License No. 322 Date Necember 2 , 1974		
Gravel placed fromft. toft.	OUTSTANDED TO THE PROPERTY AND SECURITY TO		