

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

RECEIVED

STATE OF OREGON
(Please type or print)

OCT 17 1977 (Do not write above this line)

State Well No. 31S/15W-321A
State Permit No. _____

CURR 000384
984

(1) OWNER: WATER RESOURCES DEPT.
Name Charlie Ellis SALEM, OREGON
Address Box 25 Port Orford, Ore.

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: Rotary Driven
Cable Jetted
Dug Bored
(4) PROPOSED USE (check): Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED: Threaded Welded
8" Diam. from 0 ft. to 67 ft. Gage 250
" Diam. from " ft. to " ft. Gage
" Diam. from " ft. to " ft. Gage

PERFORATIONS: Perforated? Yes No.
Type of perforator used _____
Size of perforations in. by in.
perforations from " ft. to " ft.
perforations from " ft. to " ft.
perforations from " ft. to " ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name Johnson
Type Stainless steel Model No. telescope
Diam. 8 Slot size .045 Set from 65'-7" ft. to 71'-6" ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Bailer test 30 gal./min. with 4 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered " ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite & cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 4 sacks
How was cement grout placed? 2 sacks bentonite
Grouted from surface
Was a drive shoe used? Yes No Plugs _____ Size: location _____ ft.
Did any strata contain unusable water? Yes No
Type of water? _____ depth of strata _____
Method of sealing strata off _____
Was well gravel packed? Yes No Size of gravel: _____
Gravel placed from _____ ft. to _____ ft.

(10) LOCATION OF WELL:
County Curry Driller's well number _____
NE 1/4 SW 1/4 Section 32 T31S R. 15W W.M.
Bearing and distance from section or subdivision corner _____

(11) WATER LEVEL: Completed well.
Depth at which water was first found 20 ft.
Static level 15'-10" ft. below land surface. Date 9-26-77
Artesian pressure lbs. per square inch. Date _____

(12) WELL LOG: Diameter of well below casing 0
Depth drilled 72 ft. Depth of completed well 71 1/2 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Clay soil black	0	1	
Sand hard gray	1	2	
Sand hard brown	2	5	
Sand with peat dark brown	5	20	
Fine gravel blue	20	25	
Medium sand blue	25	27	
Silt blue	27	63 1/2	
Gravel with sand medium	63 1/2	72	

Work started 9-23 1977 Completed 9-26 1977
Date well drilling machine moved off of well 9-26 1977

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Andrew Miller Date 10-11, 1977
(Drilling Machine Operator)
Drilling Machine Operator's License No. 469

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Bill Miller Well Drilling
(Person, firm or corporation) (Type or print)
Address Route 1, Box 1115 Bandon, Oregon 97411
[Signed] Andrew Miller
(Water Well Contractor)
Contractor's License No. 600 Date 10-11, 1977