File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

State Permit No.

SADEM, OMEGON		
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level lowered below static level	el is
Name School Dist, 3C1,	Was a pump test made? Yes You If yes, by whom?	
Address Langolis, Port Orford High Sel	Yield: gal./min. with ft. drawdown after	hrs.
Langolis, Ore	n n n	**
(2) LOCATION OF WELL:	Bailer test /2 gal./min. with /8 ft. drawdown after	" hrs.
County Cu 184 Owner's number, if any-	Artesian flow g.p.m. Date	
1/4 1/4 Section T. R. W.M.	Temperature of water 5 4 Was a chemical analysis made?	Yes No
Bearing and distance from section or subdivision corner	Temperature of water 3 2 was a chemical analysis made.	103 2 110
NE 1/4 SW 1/4 Sec 34	(III) WILLIAM INCO.	inches.
T. 1 21 1 Pares 15	Depair drined TD 11 2 3 5 5 5 5 5	
10 whomps of the large to	Formation: Describe by color, character, size of material and str show thickness of aquifers and the kind and nature of the mate stratum penetrated, with at least one entry for each change of	rial in each
	MATERIAL FROM	TO
		14
(3) TYPE OF WORK (check):	yellow clay	144
New Well Deepening Reconditioning Abandon	Brown Sitty Clay 12	, 21
If abandonment, describe material and procedure in Item 11.	gray silty claye	
PROPOSED LISE (about). (5) TWDE OF WELL	Some Sand 21	25
PROPOSED USE (check): (5) TYPE OF WELL:	Coarse gray Sand	
Domestic Industrial Municipal Rotary Driven Cable Detect Cable Cable	some black wheat	
Irrigation Test Well Other Dug Bored	grainsize 25	32
	0	
(6) CASING INSTALLED: Threaded Welded	yellow sand some	_
6 "Diam. from 1 ft. to 40 ft. Gage 17"	COATSE & Some	
" Diam. from ft. to ft. Gage	0 x 7 ve 1 16"- 32	38
" Diam. from ft. to ft. Gage	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	
	Coarse black sand	
(7) PERFORATIONS: Perforated? Perforated? No		1
Type of perforator used Torch Slotted	4 Some Small graves	39
SIZE of perforations in. by / Ff. in.		
22 perforations from 28 ft. to 39-6 ft.	Hard Shale bed	-15
perforations from ft. to ft.	-rock 39	40
perforations from ft. to ft.		
perforations from ft. to ft.	water all the way	
·	from 25 Ft. to 39F/	
perforations fromft. toft.		
(8) SCREENS: Well screen installed Yes No		
(0) 5022222		
Manufacturer's Name		
-v		
Slot size Set from ft. to ft.	Work started 7/27 19 60 Completed 7/28	<u>ー・</u>
Dram. Slot size Set from ft. to ft.	Work started 7/27 19 60 Completed 7/28	19 6
(9) CONSTRUCTION:	(13) PUMP:	
Was well gravel packed? Yes No Size of gravel:	Manufacturer's Name	
Gravel placed from ft. to ft.	Type: H.P.	
Was a surface seal provided? Yes No To what depth? ft.		
Material used in seal Tob Soil -Tambed	Well Driller's Statement:	
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction and thi	s report i
Type of water? Depth of strata	true to the best of my knowledge and belief.	
Method of sealing strata off	1 1 / 1 in man of the	
MICHION OF SCHOOL STREET	NAME W. 9. (Person, firm, or corporation) (Type or p.	rint)
(10) WATER LEVELS:		
Static level 17 ft. below land surface Date 1/28/64	Address COQUILLE JOTE	L
Artesian pressure lbs. per square inch Date	Driller's well number	*****
Log Accepted by:	[Signed] M. L. Lurryston	20
	(Well Driller)	M-C
[Signed] Allen Slocus Date	License No. 67 Date 7/29	19.6
Clesk (Owner)		,