NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

## WATER WELL REPORT

## STATE OF OREGON

1806

(Please type or print)

Do not write above this line)

State Well No. 145/9E - 9 C
State Permit No.

(1) OWNER:  Name Brooks Resources Corporation  Address 416 N.E. Greenwood Ave.	(10) LOCATION OF WELL:  County Deschutes Driller's well number
Bend, Oregon 97701	34 SW 34 Section 9 T. 14S R. 9 E W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well □ Deepening □ Reconditioning ♣ Abandon □	
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found ft.
Rotary Driven Domestic Industrial Municipal Domestic	Static level ft. below land surface. Date
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded 1  10 "Diam from 1 tt to 76 ft Gage 250	(12) WELL LOG: Diameter of well below casing
" Diam, from ft. to ft. Gage	The state of the s
" Diam from	Formation: Describe color, texture, grain size and structure of materials and show thickness and nature of each stratum and aquifer penetrated with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
PERFORATIONS: Perforated?  Yes No.	
Type of perforator used Factory Perforated	MATERIAL From To SWL
Size of perforations 3/16 in. by 4 in.  560 perforations from 36 to 76	
perforations from 1t. to 1t.	Cleaned existing hole to 101 ft.
perforations from	
perforations from	
(7) SCREENS: Well screen installed?   Yes XX No	And the second s
Manufacturer's Name	
Type Model No	
Diam Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ♣ No If yes, by whom?	RECEIVED
Yield: gal./min. with ft. drawdown after hrs.	
" " "	JUN 25 1970
<i>"</i> " "	WATELLES
ailer test 10 gal./min. with ft. drawdown after hrs.	WATEL DESCRIPT
Artesian flow g.p.m.	GRECON
perature of water Depth artesian flow encountered ft.	Work started 5-31 19 Completed 6-15 19 79
( ) CONSTRUCTION:	Date well drilling machine moved off of well 6-15 139
Well seal—Material used <b>not disturbed</b>	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Date 6 /8 , 199
Number of sacks of cement used in well seal sacks	(Similar Machine Operator)
How was cement grout placed?	Drilling Machine Operator's License No.
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? 🎽 Yes 📋 No Plugs Size: location ft.	Name Orvail Buckner Well Drilling, Inc.
Did any strata contain unusable water? 🗌 Yes 🕇 No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address 1686 H.E. NEgus Way, Redmond, Ore. 97756
Method of sealing strata off	Comment ()
Was well gravel packed?  Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 698 Date 6=18 , 19.79
- Company of the control of the cont	