WATER WELL REPORT The original and first copy of this report are to be state Well No. 145/10E-3/ca STATE OF OREGON STATE ENGINEER, SALEM, OREGON 97310 N 2 1 1972 (Please type or print) within 30 days from the date State Permit No. of well completion. STATE ENC TO the mot write above this line) TOLLGATE (10) LOCATION OF WELL: (1) OWNER: KESOURCES County DESCHOTES Driller's well number 5404 NE 5004 Section 31 T. 145R. 10E Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening ☐ Reconditioning ☐ Abandon [7] If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Rotary Driven [Domestic X Industrial | Municipal | Static level ft. below land surface. Jetted [Cable Irrigation

Test Well
Other Bored Artesian pressure lbs. per square inch. Date CASING INSTALLED: Threaded | Welded (12) WELL LOG: Diameter of well below casing ... 12." Diam. from +2 ft. to 7/ ft. Gage ... Depth drilled 220 ft. Depth of completed well 10." Diam. from 57 ft. to 2/7 ft. Gage 279 Formation: Describe color, texture, grain size and structure of materials; " Diam. from _____ ft. to ____ ft. Gage ___ and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? Yes No. TORGH Type of perforator used MATERIAL. From /8 in. by Size of perforations OP SOIL AND SAND 2_ 120 perforations from ____ LAY AND GRAVEL 21 GRAVEL AND BOWDERS HARD GREET BASALT 80 perforations from 160 ft. to 180 ft. 20 perforations from 200 ft. to EAVEL AND CINDERS 20 (7) SCREENS: Well screen installed?
Yes No HARD GREY BASALT 97 70 Manufacturer's Name GIPAUEL AND CINDERS WATER BEARING LAWA Diam. Slot size _____ Set from ____ ft. to ____ ft. HARD BLACK BASACT Diam. Slot size Set from ft. to ft. RED CINDERS MET BROWN Drawdown is amount water level is lowered below static level (8) WELL TESTS: BRAKEN BROWN KOCK 104215 Was a pump test made? Yes \(\subseteq \text{No If yes, by whom?} \) HADD GREY BASAKT Yield: 600 gal./min. with 5 ft. drawdown after 48 hrs. Bailer test gal./min. with ft. drawdown after g.p.m. perature of water 52 Depth artesian flow encountered Work started HPR /8 1972 Completed WWE /3072 Date well drilling machine moved off of well (9) CONSTRUCTION: CEMENT CTROUT Drilling Machine Operator's Certification: Well seal-Material used This well was constructed under my direct supervision.

Materials used and information reported above are true to my best knowledge and belief.

[Signed]

Date June 12072 Well sealed from land surface to Diameter of well bore to bottom of seal _____in_ [Signed] (Drilling Machine Operator) Date JUNE 24972 Diameter of well bore below seal ________in, Number of sacks of cement used in well seal Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? Yes 🗆 No Plugs Size: location ft. STRASSER Did any strata contain unusable water?

Yes No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [Yes No Size of gravel: Contractor's License No. 10 Date 10 NE 50 Gravel placed from

NOTICE TO WATER WELL CONTRACTOR