

NOTICE TO WATER WELL CONTRACTOR  
The original and first copy  
of this report are to be  
filed with the

RECEIVED  
OCT 13 1971

WATER WELL REPORT

DESC  
2088

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310  
within 30 days from the date  
of well completion. SALEM, OREGON

STATE ENGINEER (Please type or print)

(Do not write above this line)

State Well No. 14/12-17 bc  
State Permit No.

(1) OWNER:

Name Double R & C Ranch  
Address P.O. Box 238 Terrebonne, Ore

(2) TYPE OF WORK (check):

New Well  Deepening  Reconditioning  Abandon   
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary  Driven   
Cable  Jetted   
Dug  Bored

(4) PROPOSED USE (check):

Domestic  Industrial  Municipal   
Irrigation  Test Well  Other

CASING INSTALLED:

1/6" Diam. from 0 ft. to 20 ft. Gage 250  
" Diam. from ft. to ft. Gage  
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated?  Yes  No.

Type of perforator used  
Size of perforations in. by in.  
perforations from ft. to ft.  
perforations from ft. to ft.  
perforations from ft. to ft.

(7) SCREENS:

Well screen installed?  Yes  No

Manufacturer's Name  
Type Model No.  
Diam. Slot size Set from ft. to ft.  
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level  
Lower Bridge Farm Supply

Was a pump test made?  Yes  No If yes, by whom?  
Yield: 1150 gal./min. with 100 ft. drawdown after 20 hrs.  
" " " "  
" " " "  
Bailer test gal./min. with ft. drawdown after hrs.  
Artesian flow g.p.m.

Temperature of water 57 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement  
Well sealed from land surface to 20 ft.  
Diameter of well bore to bottom of seal 1.8 in.  
Diameter of well bore below seal 1.6 in.  
Number of sacks of cement used in well seal 6 sacks  
Number of sacks of bentonite used in well seal sacks  
Brand name of bentonite  
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.  
Was a drive shoe used?  Yes  No Plugs Size: location ft.  
Did any strata contain unusable water?  Yes  No  
Type of water? depth of strata  
Method of sealing strata off  
Was well gravel packed?  Yes  No Size of gravel:  
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Deschutes Driller's well number 9  
SW 1/4 NW 1/4 Section 17 T. 14S R. 12E W.M.  
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 198 ft.  
Static level 150 ft. below land surface. Date 3/68  
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 16"  
Depth drilled 260 ft. Depth of completed well 260 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Overburden	0	35	
Red sandstone	35	82	
Brown sandstone	82	155	
Water bearing sand	155	157	
Brown sandstone	157	246	
Water bearing sand	246	260	

Work started 2/10 1968 Completed 2/25 1968  
Date well drilling machine moved off of well 2/25 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] [Signature] Date 2/25, 1968  
(Drilling Machine Operator)

Drilling Machine Operator's License No.

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Double R & C Ranch  
(Person, firm or corporation) (Type or print)

Address P.O. Box 238 Terrebonne, Oregon

[Signed] [Signature] (Water Well Contractor)

Contractor's License No. Date, 19...