## WATER WELL REPORT STATE OF OREGON

## RECEIVED

SEP 0 9 1980

State Well No. 145/12E-21

	<b>)</b>	
)	ATER RESOURCES	DEPT
	CALEN OPEGON	

:	1.
State Permit No.	

JACKET STATE OF THE STATE OF TH	
1) OWNER:	(10) LOCATION OF WELL:
Jack Lidell	County Deschutes Driller's well number
ddress 2914 S.W. Canal	½ ½ Section 21 T.14S R. 12E W.M.
ity Redmond State Ore. 97756	Tax Lot # Lot Blk Subdivision
2) TYPE OF WORK (check):	Address at well location:
Alaman D	
Iew Well ☑ Deepening □ Reconditioning □ Abandon □  f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
	Depth at which water was first found 90 ft.
3) TYPE OF WELL: (4) PROPOSED USE (check):	Static level 90 ft. below land surface. Dat8-28-80
Air T Driven Domestic X Industrial Municipal I Industrial Division I Test Well Dother D	Artesian pressure lbs. per square inch. Date
totary Mud	(12) WELL LOG: Diameter of well below casing
5) CASING INSTALLED: Steel  Plastic	Depth drilled 130 ft. Depth of completed well 120 ft.
Threaded  Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry
	for each change of formation. Report each change in position of Static Water Level
"Diam. from	and indicate principal water-bearing strata.
LINER INSTALLED:	MATERIAL From To SWL
"Diam. from ft. to ft. Gauge	Brown Sandstone 0 53
	Red Sandstone 53 87
PERFORATIONS: Perforated?   Yes X No	Water-Bear. Brown Conglomerate 87   130
Type of perforation sed in. by in.	
Size of perforations in. by in.  perforations from	
perforations from	
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? ☐ Yes X No	
Manufacturer's Name	
TypeModel No	
Diam. Slot Size Set from ft. to ft.	
Diam. Slot Size Set from ft. to ft. to Drawdown is amount water level is lowered	
WELL TESTS: below static level	
Was a pump test made? ☐ Yes ☒ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	
" Blow Test- 200 GPM " "	
gal./min. with drill stem at ft. hrs.	
her test 20 gal./min. with 0 ft. drawdown after 1 hrs.	
Artesian flow g.p.m.	
Temperature of water 50% Depth artesian flow encountered ft.	Work started 8-27 1980 Completed 8-27 1986
(9) CONSTRUCTION: Special standards: Yes □ No 🕅	Date well drilling machine moved off of well 8-27- 19 86
Seal—Material used Cement	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision. Materials use
Diameter of well bore to bottom of seal12 in.	and information reported above are true to my best knowledge and belief
Diameter of well bore below sealin.	(Drifting Machine Operator)
Number of sacks of cement used in well seal	Drilling Machine Operator's License No
How was cement grout placed? Pressure Grouted	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true
	the best of my knowledge and belief.
Was pump installed?	Name Orvail Buckner Well Drilling, Inc.
Was a drive shoe used? ☐ Yes K No Plugs Size: location ft.	(Person, firm or corporation)  Address 1525. N.E. Neglis. Way. Redmond, Ore 977.56
Did any strata contain unusable water?   Type of Water?   depth of strata	Address 1900
2,750 02 11.000	[Signed] (Water Well Contractor)
Method of sealing strata off  Was well gravel packed? □ Yes ▼ No Size of gravel:	Contractor's License No. 608 Date 8-28 , 1980
Gravel placed from	Contractor of License 1101
Graver placed from	