NOTICE TO WATER WELL CONTRACTOR The original and first copy of this per CE VEER WELL are to be filed with the	$\mathcal{A}$ 1 $I$	145/DE-25
WATER RESOURCES DEPARTMENT SEP 191978 STATE OF CONTROL SALEM, OREGON 97310 SEP 191978 (Please type	OREGON State Well No.	110100 200
SALEM, OREGON 97310 SEP 13 1370 (Please type within 30 days from the date	or print) DES	),,
of well completion. WATER RESOURCE Phonor write and	ove this line	
SALEM, OREGON		
(1) OWNER:	(10) LOCATION OF WELL:	
Name Mr. Douglas C. Watson	County Deschutes Driller's well nu	mber
Address 5023 NW Dahl Lane	NE 14 SE 14 Section 25 T. 14 S R. 12 E W.M.	
Redmond, Oregon 97756	Bearing and distance from section or subdivision	n corner
(2) TYPE OF WORK (check):		
New Well		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 135 ft.	
Rotary Driven Domestic M Industrial Municipal	Static level 105 ft. below land st	urface. Date 2/9/78
Cable	Artesian pressure lbs. per square	
Dotted   Mangarata   State   S	Artesian pressure 165, per square	- Mon. Dave
(5) CASING INSTALLED: Threaded □ Welded □	(12) WELL LOG: Diameter of well b	elow casing
6 " Diam. from +1 ft. to 19 ft. Gage 250	Depth drilled 155 ft. Depth of comple	A
ft. Gageft.	Formation: Describe color, texture, grain size a	
ft. Gage	and show thickness and nature of each stratus	m and aquifer penetrated,
(C) DEDUCE A TYONG.	with at least one entry for each change of format position of Static Water Level and indicate prin	
(6) PERFORATIONS: Perforated?   Yes   No.		
Type of perforator used	MATERIAL	
Size of perforations in. by in.	Overbunden	0 1
perforations from ft, to ft.	Lava - Mild	1 70
perforations from ft. to ft.	Basalt = Gray	70 100
perforations from ft. to ft.	Sandstone - Brown	100 140 105
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	Lava - Mild	140 155
Manufacturer's Name		
TypeModel No.		
Diam. Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes ☑ No If yes, by whom?		
d: gal./min. with ft. drawdown after hrs.		
" " " "		
n n n n	-	
Bailer test 20 gal./min. with 0 ft. drawdown after 1 hrs.		
esian flow g.p.m.		<u> </u>
Temperature of water 51 Depth artesian flow encountered ft.	Work started 2/9/78 19 Complete	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	2/9/78 19
Well seal—Material used Cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to 19 ft,	This well was constructed under my	direct supervision.
Diameter of well bore to bottom of seal10in.	Materials used and information reported best knowledge and hellef.	above are true to my
Diameter of well bore below seal		Date 2/24/78, 19
Number of sacks of cement used in well seal	(Drilling Machine Operator)	
How was cement grout placed? Gravity Flow	Drilling Machine Operator's License No.	1148
in the state of th	Water Well Contractor's Certification:	
	This well was drilled under my jurisd true to the best of my knowledge and bel	
Was a drive shoe used? ☐ Yes 🖫 No Plugs Size: location ft.	Name Davidson Drilling Inc.	
Did any strata contain unusable water? 🗌 Yes 🙀 No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address P.O. Box 315 Redmond, 0	re. 97756
Method of sealing strata off	[Signed] 7 Sorton Dan	oso
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	[Signed] (Water Well Control	ractor)
Gravel placed fromft. toft.	Contractor's License No. 548 Date	2/24/78 , <sub>19</sub>