NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date of well completion.

DESC 2188

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

State Well No. 14S/12E-36cc
State Permit No.

(1) OWNER:
Name Mountain Heights Investment Co.
Address 17950 Richardson Rd, Dallas, Or 97330

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
8" Diam. from +1 ft. to 20 ft. Gage 250
5" Diam. from 0 ft. to 222 ft. Gage 188
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☒ Yes ☐ No
Manufacturer's Name Johnson
Type Stainless Steel Model No. 120
Diam. 5" Slot size 20,000 Set from 222 ft. to 232 ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 22 gal./min. with no ft. drawdown after 1 hrs.
Artesian flow none g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Portland Cement Type I
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed? Pressure Pumped
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Deschutes Driller's well number 81
SW ¼ SW ¼ Section 36 T. 14S R. 12E W.M.
Bearing and distance from section or subdivision corner
~~Lot # 5, Woody Acres, About 15' from East line, and 25' from the South line.~~

(11) WATER LEVEL: Completed well.
Depth at which water was first found 202 ft.
Static level 202 ft. below land surface. Date 11-18-80
Artesian pressure none lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8"
Depth drilled 232 ft. Depth of completed well 232 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sandy Topsoil	0	2	
Black Basalt	2	50	
Brown Sandstone	50	151	
Black Sandstone	151	171	
Black Sand WB	171	232	202

RECEIVED
DEC 30 1980
WATER RESOURCES DEPT
SALEM, OREGON

Work started 11-4-80 19 Completed 11-18-80 19
Date well drilling machine moved off of well 11-28-80 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Bill Williams (Drilling Machine Operator) Date 11-25-80 19
Drilling Machine Operator's License No. 1231

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Bill Williams Well Drilling (Person, firm or corporation) (Type or print)
Address P.O. Box 334, Redmond, Or 97756
[Signed] (Water Well Contractor)
Contractor's License No. 713 Date 11-29-80, 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119