NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report

are to be filed with the

WATER WELL REPORT

STATE OF OREGON

State	Well	No.	145	-132	-16	رمي
			^			
State	Pern	nit N	ro. Le	cond	Não.	red

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 STATE OF (Please type				
within 30 days from the date of well completion. (Do not write ah	ove this line) State Permit	No. 4C	oriou	~~071.04
(1) OWNER:	(10) LOCATION OF WELL:			
Name Terrebonne Water District	County Deschutes Driller's well	number		
Address Terrebonne, Ore. 97760	SE 14 SW 14 Section 16 T. 14S	R. 13	E	W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivi	sion corne	er	
New Well ☐ Deepening ☐ Reconditioning My Abandon ☐				
If abandonment, describe material and procedure in Item 12.			***************************************	
	(11) WATER LEVEL: Completed	well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 25			ft.
Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted Jetted	Static level 256 ft. below land	surface.	Date 1	-55-8T
Bored Irrigation Test Well Other	Artesian pressure lbs. per squ	are inch.	Date	
(5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well	below ca	sing 0	
10 "Diam. from 2 ft. to —25 ft. Gage 250	Depth drilled 378 ft. Depth of com		്രസ	8 _{ft.}
8 "Diam from 1 ft. to 377 ft. Gage 188	Formation: Describe color, texture, grain size			
" Diam. from ft. to ft. Gage	and show thickness and nature of each strat with at least one entry for each change of form			
(6) PERFORATIONS: Perforated? M Yes \(\square\) No.	position of Static Water Level and indicate pr			
Type of perforator used factory	MATERIAL	From	То	swL
Size of perforations ‡ in. by 4 in.	brown sandy soil	0	2	
	brown coarse sandstone	2	88	
160	hard grey rock	8	60	<u> </u>
perforations from ft. to ft.	soft brown sandstone	60	170	0.56
(7) SCREENS: Well screen installed? Yes X No	hard broken rock	170	258	256
Manufacturer's Name	med. sand & gravel W.B. brown soft sandstone	2 <i>5</i> 8 269	269 318	
Type Model No.	coarse brown sand & gravel	318	378	
Diam. Slot size Set from ft. to ft.	WB		770	
Diam Slot size Set from ft. to ft.				<u> </u>
(8) WELL TESTS. Drawdown is amount water level is				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	DECEMEN	 	ļ	ļ
a pump test made? Yes No If yes, by whom?	<u> REGEIVEU</u>	 	ļ	
Yield: gal./min. with ft. drawdown after hrs.	JAN2 8 1981		ļ <u>.</u>	
<i>"</i> " " "	WATER RESOURCES DEPT	1		
" " "	Maging Class Committee Com			
per test 15 gal./min. with no ft. drawdown after 1 hrs.	SALEM, CRECON			
exessian flow g.p.m.		<u> </u>		
Temperature of water Depth artesian flow encountered ft.	Work started 1-16 1981 Comple		22	19 81
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1	22	1981
Well seal—Material used cement	Drilling Machine Operator's Certification	1:		_
Well sealed from land surface toft	This well was constructed under m			
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	1 above	are tru	e to my
Diameter of well bore below seal in.	[Signed] Dale Drue	. Date	1-26	₁₉ 81
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	الدم		•
How was cement grout placed? pressure grout	Drilling Machine Operator's License No.	9 <i>3</i> 4		•••••
	Water Well Contractor's Certification:			
The state of the s	This well was drilled under my juris		nd this	report is
Was a drive shoe used? Yes No Plugs Size: location ft.	true to the best of my knowledge and b			
Did any strata contain unusable water? Yes X No	Name Crawford Well Drilling, (Person, firm or comporation)	(T	ype or pr	int)
Type of water? depth of strata	Address 1245 Lower Bridge Terre			
Method of sealing strata off	1 V / ~	7 1		
Was well gravel packed? [] Yes X No Size of gravel:	[Signed] (Water Well Co	tractor)		
Charles and the second	Contractor's License No. 570 Date	* · · · ·	1-26	1081