## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

ECEIVATE DESC 386

AUG 27 1968 ATE OF OREGON

AUG 27 1968 ATE OF OREGON

STATE ENGINEER, SALEM, OREGON TATE ENGINEER ype or print) within 30 days from the date of well completion.

SALEM OREGON

State Well No. 14/13-16 D

State Permit No. .....

(1) OWNER!	(11) LOCATION OF WELL:	
Name Synton Succession	County Descrites Driller's well number	
Address Rodmand Onegon	NW 4 NU14 Section 16 T. 145R. 13 E	W.M.
(2) TOUR OF MORE (1. 1)	Bearing and distance from section or subdivision corner /03/	
(2) TYPE OF WORK (check):	Sayetheast of NW Corner spoterin alon	gees
New Well Deepening Reconditioning Abandon	Theres Budge word aprex 1500	75
If abandonment, describe material and procedure in Item 12.	for north	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing 8 "	
Cable Jetted   Domestic   Industrial   Municipal	Depth drilled 190 ft. Depth of completed well 180	ft.
Dug Bored   Irrigation Test Well Other	Formation: Describe color, texture, grain size and structure of mate	
CASING INSTALLED: Threaded Welded	and show thickness and nature of each stratum and aquifer peneti	rated,
	with at least one entry for each change of formation. Report each ci in position of Static Water Level as drilling proceeds. Note drilling	
		WL
" Diam. from ft. to ft. Gage	BROWN SANDY SOIL 0 5	
PERFORATIONS: Perforated?   Yes   No.	RED SOFT SANDSTONE 5 13	
Theme of words and a	GREY HARD ROCK 13 55	
	BROWN SOFT SANDSTONE 55 85	
	GREY HARD SANDSTONE 85 122	
perforations fromft. toft.	BROWN, SOFT SANDSTONE 122 155	
perforations fromft. toftftft.	COURSE BLACK SAND	
perforations fromft. toft.	WATER BEARING) 155 178	
perforations fromft. toft.	HARD GREP ROCK 178 180	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No		
Manufacturer's Name		
Type Model No.	*	
Diam.       Slot size       Set from       ft. to       ft.         Diam.       Slot size       Set from       ft. to       ft.		
(8) WATER LEVEL: Completed well.	·	_
Static level / 50 ft. below land surface Date 8-15-69		
Arcesian pressure lbs. per square inch Date		ž
(9) WELL TESTS: Drawdown is amount water level is		
lowered below static level		
Was a pump test made? ☐ Yes A No If yes, by whom?	Work started Q - 8 1968 Completed Q -/5 1	46B
gui, min. with 11. diawdown after firs.		
" "	sace were driving inactime moved out of weit 3-73	<u>68</u>
Bailer test aprof 20 gal./min. with 0 ft. drawdown after 1 hrs.	Drilling Machine Operator's Certification:	
Bailer test 7 20 gal./min. with 6 ft. drawdown after hrs.	This well was constructed under my direct supervision. M rials used and information reported above are true to my	ate- best
Artesian flow g.p.m. Date	knowledge and kelief	
Temperature of water 52/ Was a chemical analysis made?   Yes No	[Signed] Date Date Date 3, 19	68
(10) CONSTRUCTION:	1.14	
Well seal-Material used beatente or driet cuttings	Drilling Machine Operator's License No. 440	
Depth of seal 20 Lest ft	Water Well Contractor's Certification:	
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report	rt is
Were any loose strata cemented off? Tyes No Depth	true to the best of my knowledge and belief.	
Was a drive shoe used? ☐ Yes 📉 No	NAME CRAUFORD WELL ORILLING (Person, firm or corporation) (Type or print)	
Did any strata contain unusable water?   Yes No		
Type of water? depth of strata	Address BOX 17 FREE BONNE COE	
Method of sealing strata off	[Signed of the Constitution of the Constitutio	
Was well gravel packed? ☐ Yes W No Size of gravel:	(Water Well Contractor)	•
Gravel placed from ft. to ft.	Contractor's License No. 45/ Date 8-25 19	५ 🖇