

The original and first copy of this report are to be filed with the

RECEIVED FEB 9 - 1972

WATER WELL REPORT

STATE OF OREGON

State Well No. 14/13-2000

14/13-2000

STATE ENGINEER, SALEM, OREGON

within 30 days from the date of well completion.

STATE ENGINEER SALEM, OREGON

(Please type or print)

(Do not write above this line)

State Permit No.

APPL. 6-10207

2446 DESC 6

(1) OWNER: STACY JOHNSON 5179 N Hwy 97 READING ORE

(2) TYPE OF WORK (check): New Well [x] Deepening [ ] Reconditioning [ ] Abandon [ ]

(3) TYPE OF WELL: Rotary [ ] Driven [ ] Cable [x] Jetted [ ] Dug [ ] Bored [ ] (4) PROPOSED USE (check): Domestic [ ] Industrial [ ] Municipal [x] Irrigation [ ] Test Well [ ] Other [ ]

CASING INSTALLED: 8" Diam. from 2 ft. to 198 ft. Gage 250

PERFORATIONS: Perforated? [x] Yes [ ] No. Type of perforator used Touch. Size of perforations 7/8 in. by 12 in. 150 perforations from 138 ft. to 198 ft.

(7) SCREENS: Well screen installed? [ ] Yes [x] No. Manufacturer's Name. Type. Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level. Was a pump test made? [x] Yes [ ] No. Yield: 125 gal./min. with 7 ft. drawdown after 72 hrs.

(9) CONSTRUCTION: Well seal—Material used cement grout. Well sealed from land surface to 9.6 ft. Diameter of well bore to bottom of seal 12 in. Diameter of well bore below seal 10 in. Number of sacks of cement used in well seal 10 yds. Number of sacks of bentonite used in well seal none. Brand name of bentonite. Number of pounds of bentonite per 100 gallons of water. Was a drive shoe used? [ ] Yes [x] No. Plugs. Size: location ft. Did any strata contain unusable water? [ ] Yes [x] No. Type of water? depth of strata. Method of sealing strata off. Was well gravel packed? [ ] Yes [x] No. Size of gravel. Gravel placed from ft. to ft.

(10) LOCATION OF WELL: County Deschutes Driller's well number SW 1/4 SW 1/4 Section 20 T. 14 R. 13E W.M. Bearing and distance from section or subdivision corner North East Corner of Burtles Estate West 17

(11) WATER LEVEL: Completed well. Depth at which water was first found 128 ft. Static level 134 ft. below land surface. Date 1-12. Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 0. Depth drilled 198 ft. Depth of completed well 198 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Entries include: Brown sandy soil (0-2), Red coarse cinders (2-89), Red rock - med hard (89-93), Red hard rock (93-111), Gray hard rock (111-128), Broken black hard rock (128-198) (water bearing).

Work started 11-12-1972 Completed 1-12-1972. Date well drilling machine moved off of well 1-12-1972

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Larry Crawford (Drilling Machine Operator) Date 1-13, 1972. Drilling Machine Operator's License No. 678.

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name CRAWFORD WELL DRILLING (Person, firm or corporation) (Type or print) Address Box 17, TERREBONNE CORE 97760. [Signed] Bob Crawford (Water Well Contractor). Contractor's License No. 451 Date 1-13, 1972.