NOTICE TO WATER WELL CONTRACTOR The original and fir 1 bp G G F of this report are tripe filed with the JUL 15 1971 STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date G F F F F F F F F F F F F F F F F F F	OREGON State Well No.	14/13-21
(1) OWNER:	(10) LOCATION OF WELL:	
Name LES CNAIN	County DESC Driller's well no	ımber
Address NEDMOND-TENNERONNE ORL	1/4 1/4 Section 2 / T. /4.	(R. /3 C. W.M.
	Bearing and distance from section or subdivisi	on corner
(2) TYPE OF WORK (check):		
New Well Deepening Reconditioning Abandon		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 165 ft.	
Rotary Driven Domestic Municipal Domestic Municipal Domestic	Static level /5.5 ft. below land surface. Date (-30.5)	
Cable Jetted I Irrigation Test Well Other I	Artesian pressure lbs. per squar	re inch. Date
CASING INSTALLED: Threaded Welded Welded Medical We	(12) WELL LOG: Diameter of well below casing S Depth drilled /6 2 ft. Depth of completed well /8 2 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.	
Type of perforator used TONEL	MATERIAL	From To SWL
Size of perforations in. by in.	OVERBURDEN	V S
80 perforations from 150 ft. to 180 ft.	RED CINDERS	3 76
perforations fromft. toft.	HADD 17ED 120CK	16 28
perforations from	BLK CINDENS	28 96
	DED CINDERS	96 165
(7) SCREENS: Well screen installed? ☐ Yes 🔀 No	WATEN MEANING	
Manufacturer's Name	eon 6	165 182 155
Type Model No Diam Slot size Set from ft. to ft.		
Diam. Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ¥Yes □ No. If yes, by whom? SELF		
Yield: / 3 C gal./min. with WOft. drawdown after 45 hrs.		
	-	
Bailer test 3 0 gal./min. with 10 ft. drawdown after / hrs.		
Artesian flow g.p.m.		
Temperature of water \(\frac{\psi}{2} \) Depth artesian flow encountered ft.	Work started 6 · 30 ~ 19 1/Complet	ed 7 - 19)
(9) CONSTRUCTION:	Date well drilling machine moved off of well	<u> </u>
Well seal-Material used CEMENT - BENTONITE	Drilling Machine Operator's Certification:	
Well sealed from land surface to 2 4 ft.	This well was constructed under my direct supervision.	
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore below seal	[Signed] John Date J., 19.)	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No	
Brand name of bentonite WESTENN	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is	
of water 600 (office) lbs./100 gals.	true to the best of my knowledge and belief.	
Was a drive shoe used? Yes No Plugs Size: location ft.	Name hning harn (Type Print)	
Did any strata contain unusable water? Yes No	Do Balling of Ula	
Type of water? depth of strata	Address T.O. O. P. Duck Buck.	
Method of sealing strata off	[Signed]	
Was well gravel packed? Yes No Size of gravel:	ا برسان	9/12 7/
Gravel placed from ft. to ft.	Contractor's License No. 1 Date	/