

The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

SEP - 5 1975

(Please type or print)

WATER RESOURCES DEPT. SALEM, OREGON

DESC 2471

State Well No. 145/13E-21

State Permit No. 6-6577

(1) OWNER:

Name Marvin Tevepaugh Address 1606 N.W. Davidson Way Redmond

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

8" Diam. from +2 ft. to -19 ft. Gage 250 6" Diam. from 0 ft. to 195 ft. Gage 188

PERFORATIONS:

Type of perforator used torch Size of perforations 1/8 in. by 12 in. 102 perforations from 155 ft. to 195 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [X] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Bailer test 13 gal./min. with 0 ft. drawdown after 1 hrs. Artesian flow g.p.m. Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement Well sealed from land surface to 19 ft. Diameter of well bore to bottom of seal 12 in. Diameter of well bore below seal 8 in. Number of sacks of cement used in well seal 12 sacks Number of sacks of bentonite used in well seal 0 sacks Brand name of bentonite Number of pounds of bentonite per 100 gallons of water lbs./100 gals. Was a drive shoe used? [] Yes [X] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Deschutes Driller's well number SW 1/4 SW 1/4 Section 21 T.14S R. 13E W.M. Bearing and distance from section or subdivision corner 150' E & 177' S of NW corner of Lot 2 Block 1 North C Acres

(11) WATER LEVEL: Completed well.

Depth at which water was first found 162 ft. Static level 143 ft. below land surface. Date 8/9/75 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0 Depth drilled 195 ft. Depth of completed well 195 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include brown soil, brown soil & bldrs, red cinders & red lava rock, brn rock med hd., brn sandstone, hd gray rock, brkn brn rock, clay congl, congl (WB), red & black cinders (WB).

Work started 8/6/ 19 75 Completed 8/9 1975 Date well drilling machine moved off of well 8/9 1975

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] W. A. Williams Date 8/15, 1975 (Drilling Machine Operator) Drilling Machine Operator's License No. 864

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Crawford Well Drilling (Person, firm or corporation) (Type or print) Address 3626 N.W. Coyner, Redmond, Ore [Signed] John J. Johnson (Water Well Contractor) Contractor's License No. 595 Date 8/15, 1975