NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date

STATE OF OREGON E CEIVES (Please type or print)

11E-13dl

not write above this line) MAR 8 1978 State Permit No. ...... of well completion. WATER PESCUPOTO

(1) OWNER:	(10) LOCATIONORECWELL:			
Name JACK LEWIS	County DESCharles Dellar's well a	E	C-H	227
Address 902 N. E DEKALB	County DESCHUFEI Driller's well number FGH 337  Www 14 SE 14 Section 13 T. 145 R. 11 EAST W.M.			
Bend, Ore 97701			_#5	<u> w.м.</u>
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivis	ion corner		
New Well 🕱 Deepening 🗌 Reconditioning 🔲 Abandon 🖂				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL C. 1 / 1			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.  Depth at which water was first found 218 ft.			
Rotary Driven Domestic Dindustrial Municipal Domestic Municipal Domestic Driven Domestic Driven Domestic Driven Domestic Driven	Static level 210 ft. below land	surface D	ata 3	
Dug ☐ Bored ☐ Irrigation ▼ Test Well ☐ Other ☐	Artesian pressure lbs. per squar			_2-70
CASING INSTALLED: Threaded   Welded   18 " Diam. from ft. to 19 ft. Gage 250 ft. Ga	(12) WELL LOG: Diameter of well brow casing 16  Depth drilled 320 ft. Depth of completed well 320 ft.			
PERFORATIONS: Perforated?  Yes XXNO.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used	MATERIAL	<del></del>		T
Size of perforations in. by in.	Top Soil	From 0	To /	SWL
perforations from ft. to ft.	Brown Lava	<del></del>	4 37	
perforations from ft. to ft.	Red Lava (hard)	1	93	
perforations from	Red Sand Stone		155	
(7) CODERNO	Black Sand Stone	<del></del>	315	210
West server installed? I ies X No	Gray Lava (hard)	<u> </u>	320	
Manufacturer's Name				
Type Model No  Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.		<b></b> _		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level かおある。 アルカー・アルカー・アルカー・アルカー・アルカー・アルカー・アルカー・アルカー・				
Yield: gal./min. with ft. drawdown after hrs.				<del></del>
				<del></del>
n n				
Bailar test 20 1 ( 1/2) 0 4				
Autorian flam				
pperature of water 54 Depth artesian flow encounteredft.				<del>,</del>
ft.	Work started 11-1 19 77 Complete	d 3-5		19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3–5		19 78
Well seal—Material usedCement Grout	Drilling Machine Operator's Certification:	,		
Well sealed from land surface toft.	This well was constructed under my	direct s	uper	vision.
Diameter of well bore to bottom of seal24 in.	Materials used and information reported best knowledge and belief.	above are	e true	to my
Diameter of well bore below seal	[Signed]	Date 3	3	1078
Number of sacks of cement used in well seal 15 sacks	(Drilling Machine Operator)			
How was cement grout placed? from bottom to top	Drilling Machine Operator's License No	200	•••••	
	Water Well Contractor's Certification:			
The second secon	This well was drilled under my jurisdic true to the best of my knowledge and beli	tion and	this re	eport is
Was a drive shoe used?   Yes X No Plugs Size: location ft.	Name Name Or Myknowledge and being	GI.		
Did any strata contain unusable water?   Ves  No	(Person, firm or corporation)	(Type	or prin	t)
Type of water? depth of strata	Address 538 S Light A	12.t		
Method of sealing strata off	[Signed] To AML 00			
Was well gravel packed? ☐ Yes X No Size of gravel:	[Signed] (Water Well Contra	ctor)	•	
Gravel placed fromft. toft.	Contractor's License No. 488 Date	3/78	/	. 19