NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED MAR 22 1978 WATER RESOURCES DEPT. STATE OF OREGON

DESC 2775

State Well No. 14S/13E-36cb

State Permit No.

(1) OWNER:
Name VERN R. POPPE
Address 3616 S. HWY 97, REDMOND, ORE.

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☐
8" Diam. from +1 ft. to 20 ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☐ Yes ☒ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 20 gal./min. with 0 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water 60° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 12 sacks
How was cement grout placed?

Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County DESCHUTES Driller's well number
NW¼ S.W¼ Section 36 T. 14S R. 13E. W.M.
Bearing and distance from section or subdivision corner
LAKE PARK ESTATES - LOT 4 - BLK 20

(11) WATER LEVEL: Completed well.
Depth at which water was first found 220 ft.
Static level 217 ft. below land surface. Date 12-27-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8"
Depth drilled 275 ft. Depth of completed well 275 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Hard Grey Lava	80	125	
Red Cinders	125	145	
Black Sand & cinders + Clay	145	220	217
Brown Sandstone	220	230	
Hard Grey Rock	230	270	
Black Sand med-Coarse	270	275	

Work started Dec 6 1977 Completed Jan 3 1978
Date well drilling machine moved off of well Jan 5 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Francis F. Bigelow Date Feb. 6, 1978
(Drilling Machine Operator)
Drilling Machine Operator's License No. 894

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Orval Buckner
(Person, firm or corporation) (Type or print)
Address 1686 N.E. Negus Rd. Redmond
[Signed] Orval Buckner
(Water Well Contractor)
Contractor's License No. 608 Date 1-5, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119