NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED FEB 13 1979 WATER RESOURCES DEPT. SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

DESC 2886

State Well No. 15S/9E-1cc
State Permit No.

(1) OWNER:
Name Harry Bea Craft
Address 1445 S.W. Greentree Circle
Lake Oswego, Ore. 97034

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
8" Diam. from 1½ ft. to 20 ft. Gage .250
6" Diam. from 3 ft. to 128 ft. Gage .188
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Factory
Size of perforations 3/16 in. by 4 in.
200 perforations from 108 ft. to 128 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? Driller
Yield: 22 gal./min. with 0 ft. drawdown after 1 hrs.
" " " "
" " " "
Bailer test 20 gal./min. with 0 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 52 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement grout
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 11 sacks
How was cement grout placed? Pressure grout
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Deschutes Driller's well number FGH 2109
SW ¼ SW ¼ Section 1 T. 15S R. 9E W.M.
Bearing and distance from section or subdivision corner
Lot 160 Cross Roads 3rd Addition

(11) WATER LEVEL: Completed well.
Depth at which water was first found 103 ft.
Static level 103 ft. below land surface. Date 2/2 1979
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 8" 8"
Depth drilled 128 ft. Depth of completed well 128 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	3	
Boulder Conglomorate	3	16	
Hard Gray Lava	16	54	
Faulted Basalt	54	69	
Gray Basalt	69	103	
Red Lava	103	106	
Red Cinders	106	128	103

Work started 11-15 1978 Completed 2-2 1979
Date well drilling machine moved off of well 2-5 1979

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Tom Gibbel (Drilling Machine Operator) Date 2-10, 1979
Drilling Machine Operator's License No. 558

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name H. & H. Drilling, Inc. (Person, firm or corporation) (Type or print)
Address 538 W. Highland Ave. Redmond 97756
[Signed] Tom Gibbel (Water Well Contractor)
Contractor's License No. 488 Date 2-10, 1979

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119